



Safety Data Sheet

Page 1 of 8

Loctite Epoxi Universal 5 min, Comp. A

SDS No. : 369593

V001.0

Revision: 28.05.2026

printing date: 28.05.2026

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: Loctite Epoxi Universal 5 min, Comp. A

Supplier:
Henkel New Zealand Ltd
2 Allens Rd
East Tamaki
Auckland, 2013
New Zealand
Phone: +64 (9) 272-6710

E-mail address of person responsible for Safety Data Sheet: SDSinfo.Adhesive@henkel.com

Emergency Telephone for Chemical Accidents: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification:

Hazard Class

Skin irritation
Serious eye irritation
Skin sensitizer
Chronic hazards to the aquatic environment

Hazard Category

Category 2
Category 2A
Category 1
Category 2

Hazard pictogram:



Signal word:

Warning

Hazard statement(s):	H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700	25068-38-6	90- $\leq$ 100 %
Non-hazardous ingredients~		remainder up to 100%

SECTION 4 FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Immediately flush skin with plenty of water (using soap, if available). Seek medical advice.
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention from a specialist.
Inhalation:	Move to fresh air. Keep warm and in a quiet place. If adverse health effects develop seek medical attention.
First Aid facilities:	Eye wash and safety shower Normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Carbon dioxide, foam, powder Fine water spray
Improper extinguishing media:	Water spray jet

Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.
Special protective equipment for fire-fighters:	Wear protective equipment. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Additional fire fighting advice:	In case of fire, keep containers cool with water spray. Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Danger of slipping on spilled product. Wear impervious gloves and chemical splash goggles. Ensure adequate ventilation. Avoid skin and eye contact.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of contaminated material as waste according to Section 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:	Gloves and safety glasses should be worn Ensure that workrooms are adequately ventilated. Avoid skin and eye contact.
Conditions for safe storage:	Keep container tightly sealed. Store in a cool, dry place. Keep away from heat and direct sunlight.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

None

Biological Exposure Indices:

None

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
------------------------------	---

Eye protection:	Tightly fitting safety goggles
------------------------	--------------------------------

Skin protection:	Use of protective coveralls and long sleeves is recommended. Nitrile rubber gloves should be worn. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
-------------------------	---

Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.
--------------------------------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent, Light yellow viscous
Odor:	Mild
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Boiling point:	> 260 °C (> 500 °F)
Flash point:	> 150 °C (> 302 °F)
(Cleveland open cup)	
Vapor pressure:	< 0.13 kPa
(no method / method unknown; 180 °C (356 °F))	
Density:	1.10 - 1.18 g/cm ³
Viscosity (dynamic):	6,000 - 8,000 cp(; 30 °C (86 °F); Method: no method / method unknown)
VOC content (2010/75/EC)	0.0 % (VOCV 814.018 VOC regulation CH)

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Avoid heating. Keep away from open flames, hot surfaces and sources of ignition. Store away from incompatible materials.
Incompatible materials:	Acids. Amines. Bases. Oxidizing agents.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	LD50 LD50	> 2,000 mg/kg > 2,000 mg/kg	oral dermal		rat rat	OECD Guideline 420 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	irritating			Weight of evidence

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	irritating			Weight of evidence

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, number average molecular weight ≤ 700 25068-38-6	negative	oral: gavage		mouse	not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

SECTION 12. ECOLOGICAL INFORMATION

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: H411 Toxic to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	LC50	1.75 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	EC50	1.7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	EC50	> 11 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	NOEC	4.2 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight $\leq$ 700 25068-38-6	3.242				25 °C	EU Method A.8 (Partition Coefficient)

SECTION 13.**DISPOSAL CONSIDERATIONS**

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14.**TRANSPORT INFORMATION****Land Transport:**

UN no.: 3082
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (Bisphenol-A Epichlorhydrin resin)
Class or division: 9
Packing group: III
Marine transport IMDG:

UN no.: 3082
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (Bisphenol-A Epichlorhydrin resin)
Class or division: 9
Packing group: III
EmS: F-A ,S-F
Seawater pollutant: Marine pollutant

Air transport IATA:

UN no.:	3082
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
Class or division:	9
Packing group:	III
Packing instructions (passenger)	964
Packing instructions (cargo)	964

Further information for transport:

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number:	HSR002670
NZIoC:	Compliant for NZIoC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:	CAS: Chemical Abstracts Service GHS: Globally Harmonized System HSNO: Hazardous Substances and New Organisms IATA : International Air Transport Association – Dangerous Goods Regulations IMDG: International Maritime Dangerous Goods code LC 50: Lethal Concentration 50% LD 50: Lethal Dose 50% STEL - Short term exposure limit TWA - Time weighted average
--------------------------------	--

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.



Safety Data Sheet

Page 1 of 9

Loctite Epoxi Universal 5 min, Comp. B

SDS No. : 369594

V001.0

Revision: 28.05.2026

printing date: 28.05.2026

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: Loctite Epoxi Universal 5 min, Comp. B

Intended use: 2-Component epoxy adhesive

Supplier:
Henkel New Zealand Ltd
2 Allens Rd
East Tamaki
Auckland, 2013
New Zealand
Phone: +64 (9) 272-6710

E-mail address of person responsible for Safety Data Sheet: SDSinfo.Adhesive@henkel.com

Emergency Telephone for Chemical Accidents: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification:

Hazard Class

Skin irritation
Serious eye damage/eye irritation
Skin sensitizer
Chronic hazards to the aquatic environment

Hazard Category

Category 2
Category 1
Category 1
Category 3

Hazard pictogram:



Signal word:

Danger

Hazard statement(s):	H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing mist/vapours. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Get immediate medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	70- < 90 %
1,3-bis[3-(dimethylamino)propyl]urea	52338-87-1	10- < 20 %
Non-hazardous ingredients~		remainder up to 100%

SECTION 4 FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Immediately flush skin with plenty of water (using soap, if available). Seek medical attention from a specialist.
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention from a specialist.
Inhalation:	Move to fresh air. Keep warm and in a quiet place. If adverse health effects develop seek medical attention.
First Aid facilities:	Eye wash and safety shower Normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Carbon dioxide, foam, powder Fine water spray
Improper extinguishing media:	Water spray jet

Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.
Special protective equipment for fire-fighters:	Wear protective equipment. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Additional fire fighting advice:	In case of fire, keep containers cool with water spray. Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Danger of slipping on spilled product. Ensure adequate ventilation. Avoid skin and eye contact. Wear impervious gloves and chemical splash goggles.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of contaminated material as waste according to Section 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:	Gloves and safety glasses should be worn Avoid skin and eye contact. Ensure that workrooms are adequately ventilated. Avoid breathing vapors or mists of this product.
Conditions for safe storage:	Keep container tightly sealed. Store in a cool, dry, well-ventilated area. Protect from direct sunlight. Temperatures between + 5 °C and + 35 °C.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

None

Biological Exposure Indices:

None

Engineering controls:	Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.
Eye protection:	For eye protection, use tightly fitted safety goggles and a face-shield
Skin protection:	Use of protective coveralls and long sleeves is recommended. Nitrile rubber gloves should be worn. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent, Light yellow viscous
Odor:	Mild
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable, Product is a liquid
Boiling point:	> 200 °C (> 392 °F)
Flash point: (no method / method unknown)	> 250 °C (> 482 °F)
Vapor pressure:	<= 0.1 mbar
Density:	1.11 - 1.13 g/cm ³
Viscosity (dynamic):	10,000 - 15,000 cp(; 30 °C (86 °F); Method: no method / method unknown)
VOC content (2010/75/EC)	0.0 % (VOCV 814.018 VOC regulation CH)

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition. Excessive heat. Store away from incompatible materials.
Incompatible materials:	This product may react with strong acids or oxidizing agents. Epoxides.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

SECTION 11 TOXICOLOGICAL INFORMATION**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	LD50 LD50	2,600 mg/kg > 10,200 mg/kg	oral dermal		rat rabbit	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	LD50 LD50	5,126 mg/kg > 2,050 mg/kg	oral dermal		rat rat	other guideline: other guideline:

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	irritating or corrosive		Human, EpiDerm™ SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	not corrosive		Human, EpiDerm™ SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	Sub-Category 1B (sensitising)	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test in vitro mammalian cell micronucleus test	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	negative			mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	NOAEL=> 500 mg/kg	oral: gavage	28 ddaily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

SECTION 12. ECOLOGICAL INFORMATION**General ecological information:**

Do not empty into drains / surface water / ground water.

Ecotoxicity: H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	LC50	87 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	EC50	12 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	EC50	> 733 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	NOEC	338 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	LC50	> 1,000 mg/l	Fish	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	EC50	93 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	EC50	> 100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	EC10	> 100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	EC50	820 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	not readily biodegradable.	aerobic	1 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 72244-98-5	1.2				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1		< 2.3	28 d	Cyprinus carpio	25 °C	OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
1,3-bis[3-(dimethylamino)propyl]urea 52338-87-1	0.817				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Dispose of as hazardous waste in compliance with local and national regulations.
Do not allow product to enter sewer or waterways.

Disposal for uncleaned package: Dispose of as hazardous waste in compliance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION**Marine transport IMDG:**

Not dangerous goods

Air transport IATA:

UN no.: 3334
Proper shipping name: Aviation regulated liquid, n.o.s. (Mercaptan polymer)
Class or division: 9
Packing group: III
Packing instructions (passenger): 964
Packing instructions (cargo): 964

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number: HSR002670

NZIoC: Compliant for NZIoC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

CAS: Chemical Abstracts Service
GHS: Globally Harmonized System
HSNO: Hazardous Substances and New Organisms
IATA : International Air Transport Association – Dangerous Goods Regulations
IMDG: International Maritime Dangerous Goods code
LC 50: Lethal Concentration 50%
LD 50: Lethal Dose 50%
STEL - Short term exposure limit
TWA - Time weighted average

Reason for issue:

First issue. involved chapters: 1-16

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.