













Part Number	1GJ 958 130-521	DIFFUSE FLOOD
Mounting	Upright or pendant.	
Voltage	Multivolt™ for optimum brightness at input voltages from 9 to 33 volts.	
Power Consumption	High: 36W Low: 4W	
Actual Light Output	3600 lumen	
Protection	Reverse polarity and transient spike protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high-pressure/steam jet cleaning)	
Cable Length	Supplied with 2.5m of sheathed multi-core cable.	
Lens Material	High impact and chemical resistant Grilamid® lens	
Spare Parts	8HG 958 128–811 HD double mount stainless steel feet (c	one pair)
Compliance	CE	<u> </u>

ILLUMINATION CHART BL470 - Diffuse Flood 1m 330 1600 330 2m 82 400 82 Spread pattern H=100° V=100° V=10



HD stainless steel mounting brackets allow 360° rotation of work lamp.

8HG 958 128-811 HD double mount stainless steel feet

BL470 LED Work Lamp - Diffuse Flood

The BL470 LED work lamp featuring a unique diffuse flood lens with a powerful light output of 3600 lumen while only consuming 36W.

The new lamp is ideal for illuminating decks, garages, workshops, trailers, caravans and other close range applications where large amounts of light are needed. The ultra-smooth spread has no harsh borders or hotspots, therefore reducing eye strain and fatigue.

Providing unmatched corrosion resistance due to an innovative thermally conductive polymer housing, and the toughness of a UV, chemical and impact resistant Grilamid® lens, the BL470 is the natural choice when exceptional durability and long term reliability in demanding environments are needed.

The new work light features Multivolt™ circuitry, operating between 9 to 33V, and can therefore be used with 12V or 24V DC supply. The dual function level (100% and 10%) is also handy for reducing power consumption during long term use. Designed with Fit and Forget durability in mind, the completely sealed BL470 is covered by a 5 year warranty.

