

Blue Xtreme Straight Radiator Hose with Xtreme Heat Technology

300°F (149°C)
High Temp Rating

Aramid
Reinforcement

Uses Standard
Clamps

Application

Designed for heavy-duty and fleet service on trucks, buses and off-road equipment.

Designed for common coolants and straight radiator connections where higher heat resistance and longer life are desired.

Construction

Tube: Black EPDM

Reinforcement: 2-ply aramid

Cover: Blue EPDM wrapped finish

Length: 3'

Specifications

Temperature Range: -40°F to 300°F (-40°C to 149°C)

SAE Specifications: SAE 20R1 D1 Standard Wall

Product Specifications: 542954, 541954

Branding: Continental Elite® Blue Xtreme STR RAD Hose

Aramid ID PN SAE 20R1 D1 WP Made in Canada

Installation: See selection of Continental connectors and clamps

Warning: Do not use for fuel or oil transfer applications.

Part #	ID (in.)	OD (in.)	Length (ft.)	Working Pressure (psi)	Weight (lbs./ft.)
57214	7/8	1 ¹⁵ / ₁₆	3	150	0.32
57216	1	1 ²³ / ₆₄	3	150	0.36
57218	1 ¹ / ₈	1 ¹ / ₂	3	150	0.40
57220	1 ¹ / ₄	1 ⁵ / ₈	3	150	0.44
57222	1 ³ / ₈	1 ⁴⁷ / ₆₄	3	150	0.47
57224	1 ¹ / ₂	1 ⁵⁵ / ₆₄	3	150	0.51
57226	1 ⁵ / ₈	2	3	150	0.55
57228	1 ³ / ₄	2 ⁹ / ₆₄	3	150	0.59
57230	1 ⁷ / ₈	2 ¹ / ₄	3	150	0.63
57232	2	2 ³ / ₈	3	150	0.66
57234	2 ¹ / ₈	2 ¹ / ₂	3	125	0.70
57236	2 ¹ / ₄	2 ⁵ / ₈	3	125	0.74

Part #	ID (in.)	OD (in.)	Length (ft.)	Working Pressure (psi)	Weight (lbs./ft.)
57238	2 ³ / ₈	2 ³ / ₄	3	125	0.78
57240	2 ¹ / ₂	2 ⁷ / ₈	3	125	0.81
57242	2 ⁵ / ₈	3	3	125	0.85
57244	2 ³ / ₄	3 ¹ / ₈	3	125	0.89
57246	2 ⁷ / ₈	3 ¹ / ₄	3	125	0.93
57248	3	3 ²³ / ₆₄	3	125	0.96
57252	3 ¹ / ₄	3 ⁴¹ / ₆₄	3	125	1.04
57256	3 ¹ / ₂	3 ²⁹ / ₃₂	3	125	1.12
57260	3 ³ / ₄	4 ⁹ / ₆₄	3	125	1.19
57264	4	4 ³ / ₈	3	100	1.27
57272	4 ¹ / ₂	4 ⁷ / ₈	3	75	1.42
57280	5	5 ³ / ₈	3	75	1.57



For hose reducers, see page 30.



For connectors and clamps, see pages 39-45.