



83mm Round LED Safety DayLights™/Front Position/ Front Direction Indicator Lamp

This LED combination lamp features an integrated Safety DayLight™, front position and front direction indicator function. The lamp features a traditional round lens that illuminates with a distinctive ring of white LEDs when used as a Safety DayLight™. This lamp eliminates the need for installation of multiple lamps. Front position lamp and front direction indicator will extinguish the Safety DayLight™ automatically.



Part Number	2108-GMD			12 VOLT	
	2108-GMD24V			24 VOLT	
Mounting	Surface mount. Single bolt 1/4" stainless UNC thread. Nut and washer supplied.				
Power Consumption		P/N 2108-GMD	P/N 2108-GMD24V		
	Safety DayLights™:	3W	4W		
	Front position:	1W	1W		
	Front indicator:	4W	4W		
Protection	Reverse polarity and transient spike circuit protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high-pressure/steam jet cleaning)				
Cable Length	Pre-wired with 2.5m of sheathed multi-core cable.				
Lens Material	High impact and chemical resistant Grilamid® lens				
Compliance	ADR 6/00: Cat 1 E24 5854	ADR 49/00 ECE R6/01	ADR 76/00 ECE R7/02	ECE R87/00	

See page 84 for mounting accessories.

83MM LAMP FUNCTIONS



LED Safety DayLights™

Front position

Front direction indicator