

Safety Data Sheet

Page 1 of 10

LOCTITE 277 HIGH STRENGTH THREADLOCKER known as 277(TM) Threadlocker High Stre

SDS No.: 153485 V001.2

Revision: 27.12.2023 printing date: 02.01.2024

IDENTIFICATION OF THE MATERIAL AND SUPPLIER SECTION 1

Product name: LOCTITE 277 HIGH STRENGTH THREADLOCKER known as 277(TM) Threadlocker

High Stre

Intended use: Anaerobic Adhesive

Supplier:

Henkel New Zealand Ltd

2 Allens Rd Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

Emergency Telephone for Chemical Accidents:

24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO). Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

GHS Classification:

Hazard Class Hazard Category Target organ

Serious eye irritation Target Organ Systemic Toxicant -

Single exposure

Category 2A Category 3

respiratory tract irritation

Hazard pictogram:

Signal word: Warning

Page 2 of 10

SDS No.: 153485 V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known

as 277(TM) Threadlocker High Stre

Hazard statement(s): H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary Statement(s):

Prevention: P261 Avoid breathing mist/vapours.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Type of preparation: Methacrylate resin based threadlocker

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
α, α-dimethylbenzyl hydroperoxide	80-15-9	1-< 3 %
N,N-Diethyl-p-toluidine	613-48-9	0.1-< 1 %
N,N-dimethyl-o-toluidine	609-72-3	0.1-< 1 %
methacrylic acid	79-41-4	0.1-< 1 %
non hazardous ingredients~		60- <= 100 %

SECTION 4 FIRST AID MEASURES

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Rinse with running water and soap.

Seek medical advice.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: If product is involved in fire extinguish with dry powder, foam or carbon dioxide.

Page 3 of 10

SDS No.: 153485 V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known

as 277(TM) Threadlocker High Stre

Decomposition products in case of Oxides of carbon.

fire: Oxides of sulfur.
Oxides of nitrogen.

Irritating organic vapours.

Particular danger in case of fire: None

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid skin and eye contact.

Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Use only in well-ventilated areas.

Avoid skin and eye contact.

Conditions for safe storage: Store in a cool, well-ventilated place.

Do not expose to direct heat. Store in sealed original container.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
METHACRYLIC ACID		20	70	-	-	-
79-41-4						

Biological Exposure Indices:

None

Page 4 of 10

SDS No.: 153485

V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known

as 277(TM) Threadlocker High Stre

Engineering controls: Ensure good ventilation/suction at the workplace.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

The use of chemical resistant gloves such as Nitrile is recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable

risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

The use of chemical resistant gloves such as Neoprene or Natural Rubber is recommended

Respiratory protection: Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: red

liquid Odor: characteristic

pH: Not applicable, Product is non-polar/aprotic.

Melting point / freezing point: Not applicable, Product is a liquid

Specific gravity: 1.1

Boiling point: $> 150 \, ^{\circ}\text{C} \ (> 302 \, ^{\circ}\text{F})$ **Flash point:** $> 100.00 \, ^{\circ}\text{C} \ (> 212 \, ^{\circ}\text{F})$

(Tagliabue closed cup) No flash point up to 100 °C165 °C (329 °F)

(Cleveland open cup)

Vapor pressure: < 0.1300000 mbar (; 20.0 °C (68 °F); 27 °C (80.6 < 5 mm hg °F); 25.0 °C (77 °F)no method / < 13 Pa method unknown; 50 °C (122 < 300 mbar

°F))

Vapor density: > 1

Density: 1.0800 g/cm3

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid: Keep away from heat, spark and flame.

Page 5 of 10

SDS No.: 153485 V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known

as 277(TM) Threadlocker High Stre

Incompatible materials: Strong acids and oxidizing agents.

copper Rust. Iron.

Oxygen scavengers. Strong alkalis. Reducing agents.

Other polymerization initiators.

Hazardous decomposition

products:

In case of fire toxic gases can be released.

Irritating vapors. Oxides of carbon.

Hazardous polymerization: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion:May be harmful if swallowed.Skin:May cause mild skin irritation.Eyes:This product is irritating to the eyes.Inhalation:May cause respiratory tract irritation.

Aggravated med.

condition:

Eye, skin, and respiratory disorders.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LC50	1.370 mg/l	inhalation	4 h	rat	not specified
80-15-9	Acute	1,100 mg/kg	dermal			Expert judgement
	toxicity					
	estimate					
	(ATE)					
N,N-Diethyl-p-toluidine	Acute	100 mg/kg	oral			Expert judgement
613-48-9	toxicity	3 mg/l	inhalation			Expert judgement
	estimate	300 mg/kg	dermal			Expert judgement
	(ATE)					
	Acute					
	toxicity					
	estimate					
	(ATE)					
	Acute					
	toxicity					
	estimate					
	(ATE)					
methacrylic acid	LD50	1,320 mg/kg	oral		rat	equivalent or similar to OECD
79-41-4	LC50	> 3.6 mg/l	inhalation	4 h	rat	Guideline 401 (Acute Oral
	Acute	3.61 mg/l	inhalation			Toxicity)
	toxicity	500 - 1,000	dermal		rabbit	OECD Guideline 403 (Acute
	estimate	mg/kg	dermal			Inhalation Toxicity)
	(ATE)	500 mg/kg				Expert judgement
	LD50					Dermal Toxicity Screening
	Acute					Expert judgement
	toxicity					
	estimate					
	(ATE)					

SDS No.: 153485 V001.2

${\color{blue} LOCTITE~277~HIGH~STRENGTH~THREADLOCKER~known~as~277(TM)~Threadlocker~High~Stre} \\$

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
α, α-dimethylbenzyl	corrosive		rabbit	Draize Test
hydroperoxide				
80-15-9				
N,N-Diethyl-p-toluidine	irritating	4 h	rabbit	OECD Guideline 404 (Acute
613-48-9	-			Dermal Irritation / Corrosion)
methacrylic acid	corrosive	3 min	rabbit	OECD Guideline 404 (Acute
79-41-4				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin
				Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
methacrylic acid 79-41-4	negative negative	inhalation oral: gavage		mouse mouse	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
methacrylic acid 79-41-4		inhalation	90 d6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

SDS No.: 153485 V001.2

${\color{blue} LOCTITE~277~HIGH~STRENGTH~THREADLOCKER~known~as~277(TM)~Threadlocker~High~Stre} \\$

SECTION 12.

ECOLOGICAL INFORMATION

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	18.84 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	3.1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	NOEC	1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min	not specified	not specified
N,N-Diethyl-p-toluidine 613-48-9	LC50	78.62 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	10.34 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	7.42 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	23.69 mg/l	Algae	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-dimethyl-o-toluidine 609-72-3 methacrylic acid	LC 50 LC50	46 mg/l 85 mg/l	Fish Fish	96 h 96 h	Fathead minnow (Pimephales promelas) Salmo gairdneri (new name:	EPA OTS 797.1400
79-41-4					Oncorhynchus mykiss)	(Fish Acute Toxicity Test)
methacrylic acid 79-41-4	NOEC	10 mg/l	Fish	35 d	Danio rerio	OECD Guideline 210 (fish early lite stage toxicity test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
methacrylic acid 79-41-4	NOEC	8.2 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC10	100 mg/l	Bacteria	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)

Page 8 of 10

SDS No.: 153485 V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known as 277(TM) Threadlocker High Stre

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
N,N-Diethyl-p-toluidine 613-48-9	not readily biodegradable.	not specified	1 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
N,N-dimethyl-o-toluidine 609-72-3	not readily biodegradable.		1 %	other guideline:
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
α, α-dimethylbenzyl		9.1		calculation		OECD Guideline 305
hydroperoxide						(Bioconcentration: Flow-
80-15-9						through Fish Test)
α, α-dimethylbenzyl	1.6				25 °C	OECD Guideline 117
hydroperoxide						(Partition Coefficient (n-
80-15-9						octanol / water), HPLC
						Method)
N,N-Diethyl-p-toluidine	3.7					QSAR (Quantitative
613-48-9						Structure Activity
						Relationship)
methacrylic acid	0.93				22 °C	OECD Guideline 107
79-41-4						(Partition Coefficient (n-
						octanol / water), Shake
						Flask Method)

DISPOSAL CONSIDERATIONS SECTION 13.

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

SECTION 14. TRANSPORT INFORMATION

SDS No.: 153485
LOCTITE 277 HIGH STRENGTH THREADLOCKER known

Page 9 of 10

V001.2 LOCTITE 2// HIGH STRENGTH I as 277(TM) Threadlocker High Stre

Dangerous Goods information:

Land Transport:

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

New Zealand regulatory information:

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

HSNO Approval Number: HSR002670

Site and Storage: Refer to the site and storage requirements for this Group Standard.

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1-16

Page 10 of 10

SDS No.: 153485 V001.2

LOCTITE 277 HIGH STRENGTH THREADLOCKER known as 277(TM) Threadlocker High Stre

us 277(1111) Imediational Ingli Suc

Date of previous issue:

16.01.2019

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.