

Safety Data Sheet

Page 1 of 7

424 20G IN JP SDS No.: 173123

V001.1

Revision: 23.01.2020 printing date: 06.07.2022

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: 424 20G IN JP

Intended use: Adhesive

Supplier:

Henkel New Zealand Ltd

2 Allens Rd Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous according to the criteria of the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

GHS Classification:

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Flammable liquids Category 4
Skin irritation Category 2
Serious eye irritation Category 2A
Target Organ Systemic Toylogat - Category 3

Target Organ Systemic Toxicant - Category 3 respiratory tract irritation

Single exposure

Hazard pictogram:



Signal word: Warning

SDS No.: 173123 Page 2 of 7

V001.1 424 20G IN JP

Hazard statement(s): H227 Combustible liquid.

H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary Statement(s):

Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Ethyl 2-cyanoacrylate	7085-85-0	60-<=100 %
non hazardous ingredients~		< 10 %

SECTION 4 FIRST AID MEASURES

Ingestion: Ensure that breathing passages are not obstructed. The product will polymerise

immediately in the mouth making it almost impossible to swallow. Saliva will slowly

separate the solidified product from the mouth (several hours).

Skin: Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a

spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate

enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage

maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eyes: If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help

to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of

cy anoacry late trapped behind the eyelid cause any abrasive damage.

SDS No.: 173123 Page 3 of 7

424 20G IN JP V001.1

> Inhalation. Move to fresh air, consult doctor if complaint persists.

First Aid facilities: Eye wash

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.

Fine water spray

Decomposition products in case of Oxides of carbon, oxides of nitrogen, irritating organic vapors.

fire:

Particular danger in case of fire: In case of fire, keep containers cool with water spray.

Special protective equipment for

fire-fighters:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Do not use cloths for moppingup. Flood with water to complete polymerization and Clean-up methods:

scrape off the floor. Cured material can be disposed of as non-hazardous waste.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

Conditions for safe storage: For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C

(35.6 - 46.4 °F)

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace exposure standards:

None

Biological Exposure Indices:

None

Engineering controls: Ensure good ventilation/suction at the workplace.

Eye protection: Wear protective glasses.

Skin protection: Wear suitable protective clothing.

The use of chemical resistant gloves such as Nitrile is recommended.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SDS No.: 173123 Page 4 of 7

V001.1 424 20G IN JP

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: colourless clear, liquid

Odor: irritating

Boiling point: > 149 °C (> 300.2 °F) **Flash point:** 80 - 93 °C (176 - 199.4 °F)

Vapor pressure: 0.6600000 mbar

(; 25.0 °C (77 °F))

Density: 1.1000 g/cm3

Solubility in water: Polymerises in presence of water.

VOC content: < 3.00 %

(2010/75/EC)

SECTION 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Conditions to avoid: No decomposition if used according to specifications.

Incompatible materials: Water, Amines, Alkalis, Alcohols.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It

is almost impossible to swallow.

Skin: Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacry lates generate heat on solidification. In rare circumstances a large drop will burn the

skin. Cured adhesive does not present a health hazard even if bonded to the skin.

Eyes: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Inhalation: Exposure to vapors above the established exposure limit results in respiratory irritation, which

may lead to difficulty in breathing and tightness in the chest.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Ethyl 2-cyanoacrylate	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7085-85-0	LD50	> 2,000 mg/kg			rabbit	Oral Toxicity)
			dermal			OECD Guideline 402 (Acute
						Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

SDS No.: 173123 Page 5 of 7 424 20G IN JP

V001.1

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	not specified

Germ cell mutagenicity:

Hazardous components	Result	Type of study/	Metabolic	Species	Method
CAS-No.		Route of	activation/		
		administration	Exposure time		
Ethyl 2-cyanoacrylate 7085-85-0	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome
		aberration test			Aberration Test)

SECTION 12. **ECOLOGICAL INFORMATION**

General ecological information: Do not empty into drains / surface water / ground water.

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0	not readily biodegradable.	aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Ethyl 2-cyanoacrylate	0.776				22 °C	EU Method A.8 (Partition
7085-85-0						Coefficient)

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised

landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

TRANSPORT INFORMATION

Dangerous Goods information:

Land Transport: Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG:

Not dangerous goods

SDS No.: 173123 Page 6 of 7

V001.1 424 20G IN JP

Air transport IATA:

UN no.: 3334

Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

Class or division: 9
Packing group: III
Packing instructions (passenger) 964
Packing instructions (cargo) 964

Additional Information IATA: Primary packs containing less than 500ml are unregulated by this

mode of transport and may be shipped unrestricted.

SECTION 15. REGULATORY INFORMATION

New Zealand regulatory information:

Classified as hazardous according to the criteria of the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017

HSNO Approval Number: Group standard HSR002657

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: STEL - Short term exposure limit

TWA - Time weighted average

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1-16

Date of previous issue: 09.02.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

SDS No.: 173123 V001.1 Page 7 of 7

424 20G IN JP