


THERMAL RANGE OF APPLICATION
 THERMISCHER ANWENDUNGSBEREICH
 GAMME D'APPLICATION THERMIQUE
 CAMPO TERMICO D'APPLICAZIONE

} -40 °C...+80 °C

RESISTANT TO	}	AIR, WATER, MINERAL OIL, PETROL, DIESELOIL, SALTS PRAY
BESTÄNDIG GEGEN		LUFT, WASSER, MINERALÖL, BENZIN, DIESELÖL, SALZSPRÜHNEBEL
RESISTANT A		AIR, EAU, HUILE MINÉRALE, ESSENCE, GASOIL, BROUILLARD SALIN
RESISTENTE A		ARIA, AQUA, OLIO MINERALE, BENZINA, GASOIL, NEBBIA SALINA



General Specification: JED-334-0 DIN 16901-150					Copyright WABCO®		WABCO							
Further Technical Data:					Date		Signature		CABLE WITH SOCKET KABEL MIT GERAETESTECKDOSE CABLE AVEC PRISE DE COURANT CAVO CON PRESA DI CORRENTE					
Doc. Code:		Sheet: To			Drawn		1999-05-10						Hornischmacher	
General Tolerances JED-261					Checked		1999-05-10						Hoefler	
Range of Nominal Dimensions (± mm) Class 1) ≤ 50 > 50 ≤ 180 > 180 ≤ 400 > 400 					Expert									
					Hoefler									
					Mass		Scale		Material No.					
Fine					/		1:1		WABCO Id. No.: 4494250000					
Medium					KG		1:2 2:1		Doc. Code Language Sheet					
Coarse					Size		TRI		449 425 000 0					
Tapped Holes acc.					A 2		650				Function Code	CAD System	Prod.Type	Replacement for
1) Tolerance Class Applied Crossmarked									Pro/E		1 1 X			
											653	en/de fr/it	1/1	

WABCO

CABLE WITH SOCKET
KABEL MIT GERAETESTECKDOSE
CABLE AVEC PRISE DE COURANT
CAVO CON PRESA DI CORRENTE

449 425 000 0

	000	fr/it	fr/it
--	-----	-------	-------

[illegible]

Pro/E	1 1 X
-------	-------