

# **Safety Data Sheet**

660 Quick Metal® Retaining Compound

Page 1 of 13

SDS No.: 164196

V001.3

Revision: 01.02.2023 printing date: 23.01.2024

respiratory tract irritation

IDENTIFICATION OF THE MATERIAL AND SUPPLIER **SECTION 1** 

**Product name:** 660 Quick Metal® Retaining Compound

Intended use: Anaerobic Adhesive

Supplier:

Henkel New Zealand Ltd

2 Allens Rd Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

E-mail address of person responsible for Safety Data

SDSinfo.Adhesive@henkel.com

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

#### **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005. Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

#### **GHS Classification:**

**Hazard Class Hazard Category** Target organ

Serious eye irritation Category 2A Skin sensitizer Category 1 Target Organ Systemic Toxicant -Category 3

Single exposure

Chronic hazards to the aquatic

environment

Category 4

Hazard pictogram:



Signal word:

Warning

Page 2 of 13

660 Quick Metal® Retaining Compound

SDS No.: 164196 V001.3

**Hazard statement(s):** H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H413 May cause long lasting harmful effects to aquatic life.

**Precautionary Statement(s):** 

**Prevention:** P261 Avoid breathing mist/vapours.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

**General chemical description:** Mixture

**Type of preparation:** Anaerobic Sealant

# **Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1	30- < 50 %
Silica, amorphous, fumed, crystfree	112945-52-5	1- < 10 %
α, α-dimethylbenzyl hydroperoxide	80-15-9	1- < 3 %
maleic acid	110-16-7	0.1-< 1 %
methacrylic acid	79-41-4	0.1-< 1 %
N,N-Diethyl-p-toluidine	613-48-9	0.1-< 1 %
Acetic acid, 2-phenylhydrazide	114-83-0	0.1-< 1 %
N,N-dimethyl-o-toluidine	609-72-3	0.1-< 1 %
non hazardous ingredients~	·	30- <= 60 %

## SECTION 4 FIRST AID MEASURES

**Ingestion:** Rinse mouth, do not induce vomiting, consult a doctor.

Seek medical advice.

**Skin:** Rinse with running water and soap.

Seek medical advice.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

SDS No.: 164196

V001.3

660 Quick Metal® Retaining Compound

Page 3 of 13

Medical attention and special

treatment:

Treat symptomatically and supportively.

### **SECTION 5. FIRE FIGHTING MEASURES**

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

Decomposition products in case of

fire:

Oxides of carbon.
Oxides of sulfur.

Oxides of nitrogen. Irritating organic vapours.

Particular danger in case of fire: None

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Avoid skin and eye contact.

See advice in section 8

**Environmental precautions:** Do not let product enter drains.

**Clean-up methods:** For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

## SECTION 7. HANDLING AND STORAGE

**Precautions for safe handling:** Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Refer to Technical Data Sheet

Page 4 of 13

660 Quick Metal® Retaining Compound

SDS No.: 164196 V001.3

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Workplace exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
Particulates not otherwise classified, respirable dust Respirable dust (not otherwise classified) 112945-52-5	Respirable dust.		3	-	-	-
Particulates not otherwise classified, inhalable dust Inhalable dust (not otherwise classified)	Inhalable dust.		10	-	-	-
METHACRYLIC ACID 79-41-4		20	70	-	_	-

**Biological Exposure Indices:** 

None

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not sufficient to

control airborne contamination below occupational exposure limits.

**Eye protection:** Wear protective glasses.

**Skin protection:** Wear suitable protective clothing.

Avoid skin-contact.

Nitrile rubber gloves should be worn.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

**Respiratory protection:** Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: grey liquid
Odor: Acrylic

**pH:** Not applicable, Product is non-polar/aprotic.

Melting point / freezing point: Not applicable, Product is a liquid

Specific gravity: 1.1

**Boiling point:** > 150 °C (> 302 °F) **Flash point:** > 100 °C (> 212 °F)

(Tagliabue closed cup)

**Vapor pressure:** < 7 mbar  $(; 26 \,^{\circ}\text{C} (78.8 \,^{\circ}\text{F}); 20 \,^{\circ}\text{C} (68 \,^{\circ}\text{F}))$  < 0.13 mbar

Vapor density: > 1

Density:1.098 g/cm3Solubility in water:NegligibleAuto ignition:Not available.

 ${\bf Decomposition\ temperature:}$ 

**Viscosity (dynamic):** 150,000 - 350,000 mPa.s

(; Instrument: HBT; speed of rotation: 5 min-1; Spindle No: TB; Method: ;; LCT STM 10;

V001.3

SDS No.: 164196 Page 5 of 13 660 Quick Metal® Retaining Compound

Viscosity Brookfield)

VOC content (2010/75/EC) 0 % (VOCV 814.018 VOC regulation CH)

**VOC** content: (2010/75/EC)

< 3.00 %

#### **SECTION 10.** STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

**Incompatible materials:** Reacts with strong oxidants.

Hazardous decomposition

products:

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide

and other toxic fumes.

Hazardous polymerization: None under normal processing. Polymerization may occur at elevated temperature or in

the presence of incompatible materials.

# SECTION 11 TOXICOLOGICAL INFORMATION

Page 6 of 13

# 660 Quick Metal® Retaining Compound

SDS No.: 164196 V001.3

**Health Effects:** 

Ingestion:
May be harmful if swallowed.
Skin:
May cause allergic skin reaction.
Eyes:
Causes serious eye damage.
Inhalation:
May cause respiratory tract irritation.

# Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	LD50 LD50	> 2,000 mg/kg > 5,000 mg/kg	oral dermal		rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) not specified
Silica, amorphous, fumed, crystfree 112945-52-5	LD50 LC0 LD50	> 5,000 mg/kg 0.139 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) not specified OECD Guideline 402 (Acute Dermal Toxicity)
α, α-dimethylbenzyl hydroperoxide 80-15-9	LD50 LC50 Acute toxicity estimate (ATE)	382 mg/kg 1.370 mg/l 1,100 mg/kg	oral inhalation dermal	4 h	rat rat	other guideline: not specified Expert judgement
maleic acid 110-16-7	LD50 LD50	708 mg/kg 1,560 mg/kg	oral dermal		rat rabbit	not specified not specified
methacrylic acid 79-41-4	LD50 LC50 Acute toxicity estimate (ATE) LD50 Acute toxicity estimate (ATE)	1,320 mg/kg > 3.6 mg/l 3.61 mg/l 500 - 1,000 mg/kg 500 mg/kg	oral inhalation inhalation dermal dermal	4 h	rat rat rabbit	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) Expert judgement Dermal Toxicity Screening Expert judgement
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE) Acute toxicity estimate (ATE) Acute toxicity estimate (ATE) Acute toxicity estimate (ATE)	100 mg/kg 3 mg/l 300 mg/kg	oral inhalation dermal			Expert judgement Expert judgement Expert judgement
Acetic acid, 2- phenylhydrazide 114-83-0	LD50	270 mg/kg	oral		rat	not specified

Page 7 of 13

SDS No.: 164196 V001.3

# Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	not irritating	24 h	rabbit	Draize Test
Silica, amorphous, fumed, crystfree 112945-52-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimethylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
maleic acid 110-16-7	irritating	24 h	human	Patch Test
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
N,N-Diethyl-p-toluidine 613-48-9	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

# Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
Silica, amorphous, fumed, crystfree 112945-52-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test

# Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sensitising	Guinea pig maximisat ion test	guinea pig	not specified
maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Page 8 of 13

V001.3

# Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative positive negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) Chromosome Aberration Test OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	negative negative	oral: gavage oral: gavage		mouse Drosophila melanogaster	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) not specified
Silica, amorphous, fumed, crystfree 112945-52-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro			not specified not specified not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified
maleic acid 110-16-7	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	no data with and without		Ames Test OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
methacrylic acid 79-41-4	negative negative	inhalation oral: gavage		mouse mouse	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Page 9 of 13

SDS No.: 164196 V001.3

# Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	NOAEL=300 mg/kg	oral: gavage	49 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	NOAEL=0.352 mg/l	inhalation	90 d6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
methacrylic acid 79-41-4		inhalation	90 d6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

SECTION 12. ECOLOGICAL INFORMATION

V001.3

General ecological information:

Do not empty into drains  $\slash$  surface water  $\slash$  ground water., May cause long-term adverse effects in the aquatic environment.

# **Toxicity:**

SDS No.: 164196

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methacrylic acid, monoester	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
with propane-1,2-diol 27813-02-1		Ü		.01		21,0011210
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 143 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC50	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	NOEC	> 97.2 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	EC10	1,140 mg/l	Bacteria	16 h		not specified
Silica, amorphous, fumed, crystfree	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
80-15-9 α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	18.84 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	3.1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	NOEC	1 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min	not specified	not specified
maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
maleic acid 110-16-7	EC50	42.81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic acid 110-16-7	EC50	74.35 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	,
maleic acid 110-16-7	EC10	11.8 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC10	44.6 mg/l	Bacteria	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)
methacrylic acid 79-41-4	LC50	85 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater
methacrylic acid	NOEC	8.2 mg/l	Algae	72 h	Selenastrum capricornutum	Daphnids) OECD Guideline

Page 11 of 13

V001.3

79-41-4					(new name: Pseudokirchneriella	( 0 /
methacrylic acid 79-41-4	EC50	45 mg/l	Algae	72 h	subcapitata) Selenastrum capricornutum (new name: Pseudokirchneriella	Inhibition Test) OECD Guideline 201 (Alga, Growth
					subcapitata)	Inhibition Test)
methacrylic acid 79-41-4	EC10	100 mg/l	Bacteria	17 h		not specified
N,N-Diethyl-p-toluidine	LC50	42.25 mg/l	Fish	96 h	Danio rerio	OECD Guideline
613-48-9						203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	35.2 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp.
						Acute
						Immobilisation Test)
N,N-Diethyl-p-toluidine	EC50	7.42 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
613-48-9		C				201 (Alga, Growth
NAME	1.0.50	46 0	TO: 1	0.61	F. 1	Inhibition Test)
N,N-dimethyl-o-toluidine 609-72-3	LC 50	46 mg/l	Fish	96 h	Fathead minnow (Pimephales promelas)	

# Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	readily biodegradable	aerobic	94.2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
maleic acid 110-16-7	readily biodegradable	aerobic	97.08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
N,N-Diethyl-p-toluidine 613-48-9	not readily biodegradable.	not specified	1 %	other guideline:
N,N-dimethyl-o-toluidine 609-72-3	not readily biodegradable.		1 %	other guideline:

# **Bioaccumulative potential / Mobility in soil:**

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Page 12 of 13

660 Quick Metal® Retaining Compound

SDS No.: 164196 V001.3

Methacrylic acid, monoester with propane-1,2-diol	0.97			20 °C	not specified
27813-02-1					
α, α-dimethylbenzyl		9.1	calculation		OECD Guideline 305
hydroperoxide					(Bioconcentration: Flow-
80-15-9					through Fish Test)
α, α-dimethylbenzyl	1.6			25 °C	OECD Guideline 117
hydroperoxide					(Partition Coefficient (n-
80-15-9					octanol / water), HPLC
					Method)
maleic acid	-1.3			20 °C	OECD Guideline 107
110-16-7					(Partition Coefficient (n-
					octanol / water), Shake
					Flask Method)
methacrylic acid	0.93			22 °C	OECD Guideline 107
79-41-4					(Partition Coefficient (n-
					octanol / water), Shake
					Flask Method)
N,N-Diethyl-p-toluidine	3.7				QSAR (Quantitative
613-48-9					Structure Activity
					Relationship)
Acetic acid, 2-	0.74				not specified
phenylhydrazide					
114-83-0					

## SECTION 13. DISPOSAL CONSIDERATIONS

**Waste disposal of product:** Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

## SECTION 14. TRANSPORT INFORMATION

#### **Dangerous Goods information:**

## **Land Transport:**

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

#### **Marine transport IMDG:**

Not dangerous goods

## Air transport IATA:

Not dangerous goods

# SECTION 15. REGULATORY INFORMATION

## New Zealand regulatory information:

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

**HSNO Approval Number:** HSR002670

**Site and Storage:** Refer to the site and storage requirements for this Group Standard.

Refer to the HSNO controls for approved hazardous substances.

NZIoC: Compliant for NZIOC

Page 13 of 13

SDS No.: 164196 V001.3

## SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: STEL - Short term exposure limit

TWA - Time weighted average

HSNO - Hazardous Substances and New Organisms

GHS: Globally Harmonized System CAS: Chemical Abstracts Service LD 50: Lethal Dose 50%

LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1-16

**Date of previous issue:** 02.09.2018

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.