



Specification Sheet

Forged Aluminium Alcoa Wheels

09/2018 English



Wheel size	Part no Brushed	Part no LVL ONE®	Part no Dura-Bright®	Part no Dura-Flange®	Part no Dura-Bright® Dura-Flange®	Weight (kgs)	Max. Load (kgs)	Offset (mm)	Half dual space (mm)	Disk thickness (mm)	Mounting holes diameter (mm)	Number of mounting holes	Diameter mounting hole circle (mm)	Diameter center bore (mm)	Dual mounting	Valve	Balancing weights
WorkHorse® - WorkHorse wheels are without ventholes to protect disc brakes in off-road applications, but can also be used for on road vehicles																	
22.5 x 9.00	896570	-	-	-	-	26.7	4335	154	176	22.0	32	10	335	281	yes	83MS00N	adhesive
22.5 x 11.75	818570	-	-	-	-	24.2	5000	120	-	25.3	32	10	335	281	no	40MS00N	adhesive and clip-on
FrontRunner® * - 22.5" FrontRunner® wheels offset 120mm																	
22.5 x 11.75	818560	818567	818561DB	818560DF	-	25.0	5000	120	-	25.3	26	10	335	281	no	54MS00N	adhesive and clip-on
22.5 x 11.75	818550	818557	818551DB	-	-	24.8	5000	120	-	25.3	32	10	335	281	no	54MS00N	adhesive and clip-on
FrontRunner® * - 22.5" FrontRunner® wheels offset 135mm																	
22.5 x 11.75	811520	811527	811521DB	-	-	23.5	4500	135	-	24.1	26	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	811510	811517	811511DB	-	811511DD	23.3	4500	135	-	24.1	32	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	814520	814527	814521DB	814520DF	-	26.0	5000	135	-	26.0	26	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	814510	814517	814511DB	-	-	25.8	5000	135	-	26.0	32	10	335	281	no	40MS00N	adhesive and clip-on
Trailer wheels - 19.5" & 22.5" trailer wheels																	
22.5 x 11.75	812520	812527	812522DB	-	-	21.2	4750	0	-	21.0	26	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	812510	812517	812512DB	-	-	21.0	4750	0	-	21.0	32	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	810560	810567	810562DB	-	-	24.8	5000	0	-	24.1	26	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	818560	818567	818561DB	818560DF	-	25.0	5000	120	-	25.3	26	10	335	281	no	54MS00N	adhesive and clip-on
22.5 x 11.75	818550	818557	818551DB	-	-	24.8	5000	120	-	25.3	32	10	335	281	no	54MS00N	adhesive and clip-on
22.5 x 11.75	812560	812567	812562DB	-	-	25.2	5000	45	-	25.3	26	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 11.75	812550	812557	812552DB	-	-	25.0	5000	45	-	25.3	32	10	335	281	no	40MS00N	adhesive and clip-on
22.5 x 13.00	835520	835527	835522DB	-	-	25.2	5500	-14	-	28.0	26	10	335	281	no	40MS00N	adhesive and clip-on
19.5 x 14.00	-	-	743402DB	-	-	23.7	4500	0	-	25.0	26	8	275	221	no	40MS00N	adhesive
19.5 x 14.00	-	748527	748521DB	-	-	21.6	4500	120	-	25.4	26	10	335	281	no	60MS00N	adhesive and clip-on
22.5 x 14.00	-	841517	841512DB	-	-	30.8	5800	0	-	28.5	26	10	335	281	no	40MS00N	adhesive
Wide base drive axle wheels - Important: on 2-axle vehicles TPMS and ESP																	
22.5 x 17.00	840510	-	840512DB	-	-	35.8	5800	-67	-	28.5	32	10	335	281	no	70MS07N2	adhesive

* FrontRunner®: Please consult vehicle dealer/producer in case of uncertainty which offset is applicable for your vehicle.

ARCONIC WHEEL AND TRANSPORTATION PRODUCTS

Industrieweg 135
 B-3583 Paal, Belgium
 Email: info.wheels@arconic.com
 Tel: +32 11 45 84 60
 Fax: +32 11 45 56 30
 www.alcoawheelseurope.com

Alcoa® Wheels is a product brand of Arconic.
 © 2018 Arconic Inc. or an Arconic Inc. affiliate.
 1. The Alcoa trademarks are owned by Alcoa USA Corporation and used by Arconic Inc. and its subsidiaries under license from Alcoa USA Corporation.
 Arconic reserves the right to change the information in this Specification Sheet, including the technical characteristics and designs of Alcoa® Wheels

