



HEAVY DUTY 22.5" & Above Wheel Diameter

HUB PILOT

Bolt Holes, Bolt Circle, Hub Bore	Size (in)	P/N	Replaces P/N	Approx. Weight (lbs)	Finish Options (Descriptions on back)	SURFACE TREATMENT OPTIONS				Bolt Hole Diameter	OFFSET		LOAD RATING		Valve Stem
						Dura-Black™	Dura-Bright®	Dura-Flange®	Dura-Bright® Dura-Flange®		Outset (in)	Inset (in)	Max Load (lbs)	Max Cold Infl. (psi)	
8 Holes, 275mm Bolt Circle, 221.1mm Bore	22.5 x 7.5	87340x		53	7					26mm	6.28	5.44	7300	130	005554
10 Holes 285.75mm Bolt Circle 220.1mm Bore	22.5 x 7.5	87360x		53	7					26mm	6.28	5.44	7300	130	005554
	22.5 x 8.25	ULT36x		36	1, 2, 7	BLK	1DB, 2DB			26mm	6.60	5.95	7400	130	06000
	22.5 x 8.25	ULA18x	ULT39x, ULTRAx, 88267x, 88367x	39	1, 2, 3, 7	BLK	0DB, 1DB, 2DB, 3DB			26mm	6.60	5.81	7400	130	005544, 005544BLK
	22.5 x 8.25	ULV39x	88V67x	39	7					26mm	6.60	5.81	7400	130	005544
	22.5 x 8.25	88U60x ²		44	1, 2, 7	BLK	1DB, 2DB, 3DB			26mm	6.60	5.79	7400	130	005544, 005544BLK
	22.5 x 8.25	88U67x ¹		45	1, 2, 7	BLK	1DB, 2DB			26mm	6.60	5.81	7400	130	005544, 005544BLK
	22.5 x 8.25	88U68x ²		44	1, 2, 7	BLK	1DB, 2DB			26mm	6.60	5.81	7400	130	005544, 005544BLK
	22.5 x 8.25	88U69x ²		45	1, 2, 7		1DB, 2DB			26mm	6.60	5.81	7400	130	005544
	22.5 x 8.25	88565x	88567x, 88560x	50	1, 2, 7	BLK	0DB, 1DB, 2DB	7DF	1DD, 2DD, 3DD	26mm	6.60	5.71	8050	130	005544, 005544BLK
	22.5 x 9	89U63x ⁰	89365x, 89363x	48	1, 7		1DB			26mm	N/A	3.12	10000	130	005555
	22.5 x 9	89U64x	89465x, 89464x, 89364x	56	1, 2, 3, 7	BLK	0DB, 1DB, 2DB, 3DB		3DD	26mm	6.94	5.99	10000	130	005544, 005544BLK
	22.5 x 10.5	80360x		68	1		1DB			26mm	N/A	5.50	10500	130	TR553
	22.5 x 12.25	82262x ⁰	82360x	60	7		2DB			26mm	0.56	N/A	12300	130	TR553E
	22.5 x 12.25	82362x	82365x	62	7	2BLK	2DB			26mm	3.88	N/A	12300	130	TR553E
					8	1BLK	1DB				N/A	2.75			TR553E
	22.5 x 12.25	82462x ⁰	82364x, 82366xA	66	7	BLK	1DB			26mm	N/A	4.68	12300	130	005520, 005520BLK
	22.5 x 13	83U65x	83365	63	7		2DB			26mm	3.50	N/A	13000	130	005535
					8		1DB				N/A	2.38			005555
	22.5 x 13	83462x ⁰	83364x, 83366xA	71	7		1DB			26mm	N/A	5.30	12800	130	005520
	22.5 x 14	84U61x	84U60x, 84360x, 84060x, 84267x	49	8	1BLK	1DB			26mm	0.94	N/A	12800	130	005555
					2, 7	2BLK	0DB, 2DB	7DF	2DD		N/A	0			005535
	22.5 x 14	84DV1x	84DV0x	49	7					26mm	N/A	0	12800	130	005535
	22.5 x 14	84U64x	84U62x, 84362x, 84062x, 84167x	49	2, 7	BLK	2DB			26mm	2.00	N/A	12800	130	005535
	22.5 x 14	84DV4x		49	7					26mm	2.00	N/A	12800	130	005535
	24.5 x 8.25	98U63x	98363x, 98367x, 98364x	51	1, 2, 7	BLK	0DB, 1DB, 2DB	7DF		26mm	6.60	5.77	7400	130	005554, 005554BLK
	24.5 x 8.25	98U67x ¹		55	1, 2, 7	BLK	1DB, 2DB			26mm	6.60	5.73	7300	130	005554, 005554BLK
	24.5 x 8.25	98U68x ²		54	1, 2, 7	BLK	1DB, 2DB			26mm	6.60	5.73	7300	130	005554, 005554BLK
	24.5 x 8.25	98U69x ²		55	1, 2, 7		1DB, 2DB			26mm	6.60	5.73	7300	130	005554
24.5 x 8.25	98565x	98567x, 98560x	62	1, 2, 7	BLK	0DB, 1DB, 2DB	7DF		26mm	6.60	5.61	8300	130	005554, 005554BLK	
10 Holes 335mm Bolt Circle 281.2mm Bore	22.5 x 8.25	88651x	88555x, 88455x	50	0, 7		0DB, 3DB		ODD, 3DD	32mm	6.60	5.75	8050	130	007007
	22.5 x 8.25	88652x	88557x, 88456x	50	7		0DB, 3DB		3DD	26mm	6.60	5.75	8050	130	007007
	22.5 x 8.25	88951x	88651x	45	0, 7					32mm	6.60	5.85	8050	130	005544
	22.5 x 8.25	88952x	88652x	45	0, 7					26mm	6.60	5.85	8050	130	005544
	22.5 x 9	89651x	89555x, 89455x	51	0, 7			3DB	ODD	32mm	6.93	6.08	9090	130	007007
	22.5 x 9	89652x	89553x, 89453x	51	0, 7			3DB		26mm	6.93	6.08	9090	130	007007
	22.5 x 13	83358x ⁰	83357xA	76	7			1DB		26mm	N/A	6.12	12800	130	005535

⁰ 0 and 7 finish options are determined by inset or outset mounting positions and may not be finished on both sides. See chart for position and available finish options.

¹ OEM exclusive. Purchase through Peterbilt dealer only.
² OEM exclusive. Purchase through Kenworth dealer only.