

Safety Data Sheet

Page 1 of 9

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY STICK

SDS No.: 153766

V001.2

Revision: 23.03.2021 printing date: 02.02.2022

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: LOCTITE EA 3463 known as Pipe Repair Kit EPOXY STICK

Intended use: Epoxy stick

Supplier:

Henkel New Zealand Ltd

2 Allens Rd Auckland, 2013 New Zealand

Phone: +64 (9) 272-6710

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO). Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

GHS Classification:

Hazard ClassHazard CategorySkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 1Skin sensitizerCategory 1Acute hazards to the aquaticCategory 3

Chronic hazards to the aquatic

environment

Category 3

environment

Hazard pictogram:



Signal word:

Danger

SDS No.: 153766

V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY

STICK

Hazard statement(s): H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture **Type of preparation:** Epoxy resin

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	10- < 30 %
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	3- < 5 %
non hazardous ingredients~		60- < 90 %

SECTION 4 FIRST AID MEASURES

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Immediately wash skin thoroughly with soap and water.

Seek medical advice.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

Inhalation: Move to fresh air, consult doctor if complaint persists.

First Aid facilities: Eye wash

Normal washroom facilities

 $\label{eq:medical} \textbf{Medical attention and special}$

treatment:

Treat symptomatically.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY

STICK

Improper extinguishing media: High pressure waterjet

Decomposition products in case of

fire.

Thermal decomposition can lead to release of irritating gases and vapors.

Oxides of carbon.

Oxides of nitrogen.

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid contact with skin and eyes.

Wear protective equipment.

Use personal protective equipment as described in Section 8.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal.

Dispose of contaminated material as waste according to Section 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: See advice in section 8

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided

Conditions for safe storage: Store in a cool, dry, well-ventilated area.

Do not expose to direct sunlight.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards	Workplace	exposure	standards
------------------------------	-----------	----------	-----------

None

Biological Exposure Indices:

None

Page 4 of 9

SDS No.: 153766

V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY

STICK

Engineering controls: Ventilation should effectively remove and prevent buildup of any vapor/mist/fume/dust

generated from the handling of this product.

Eye protection: Wear chemical goggles.

Skin protection: Use of protective coveralls and long sleeves is recommended.

Suitable protective gloves.

Neoprene, Butyl-rubber, or nitrile-rubber gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Metallic, Black

Putty

Odor: Mercaptan, Sulfur pH: Not applicable

Specific gravity: 2.247

Flash point: $> 93.3 \, ^{\circ}\text{C} \, (> 199.94 \, ^{\circ}\text{F})$

(Setaflash Closed Cup; ASTM

D3828 Method B)

Density: 2.25 g/cm3 **Solubility in water:** Insoluble

SECTION 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

Protect from direct sunlight.

Incompatible materials: Reaction with strong acids.

Oxidizing agents.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Oxides of carbon.

Oxides of nitrogen.

Hazardous polymerization: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Page 5 of 9

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY

STICK

Health Effects:

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Skin: Irritating to skin.

May cause an allergic skin reaction. Causes serious eye damage.

Eyes: Causes serious eye damage. **Inhalation:** May cause respiratory tract irritation.

Aggravated med.

condition:

Eye, skin and respiratory disorders.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
reaction product:	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 420 (Acute
bisphenol-A-	LD50	> 2,000 mg/kg			rat	Oral Toxicity)
(epichlorhydrin)			dermal			OECD Guideline 402 (Acute
25068-38-6						Dermal Toxicity)
2,4,6-	LD50	1,200 mg/kg	oral		rat	not specified
tris(dimethylaminomethyl						
)phenol						
90-72-2						

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	not irritating	4 h	rabbit	not specified
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
reaction product:	not irritating		rabbit	OECD Guideline 405 (Acute
bisphenol-A-				Eye Irritation / Corrosion)
(epichlorhydrin)				
25068-38-6				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY STICK

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	oral: gavage		mouse	not specified
2,4,6- tris(dimethylaminomethyl)phenol 90-72-2	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

SECTION 12. ECOLOGICAL INFORMATION

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY STICK

511011

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity:

Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
CAS-140.	type		Study	time		
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	LC50	1.75 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	EC50	1.7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	EC50	> 11 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	NOEC	4.2 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	LC50	153 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton- Buchanan (Teleostei, Cyprinidae)]
2,4,6- tris(dimethylaminomethyl)phe nol	EC50	84 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	
2,4,6- tris(dimethylaminomethyl)phe nol	NOEC	6.25 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	EC0	27 mg/l	Bacteria	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshe mm-Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
reaction product: bisphenol-A- (epichlorhydrin)	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric
25068-38-6 2,4,6-	not readily biodegradable.	aerobic	4 %	Respirometry Test) OECD Guideline 301 D (Ready
tris(dimethylaminomethyl)phe nol 90-72-2	, c			Biodegradability: Closed Bottle Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.	factor (BCF)	time			

Page 8 of 9

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY

STICK

reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	3.242		25 °C	EU Method A.8 (Partition Coefficient)
2,4,6- tris(dimethylaminomethyl)phe nol 90-72-2	-0.66		21.5 °C	EPA OPPTS 830.7550 (Partition Coefficient, n- octanol/H2O, Shake Flask Method)

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal for uncleaned package: Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14. TRANSPORT INFORMATION

Dangerous Goods information:

Land Transport:

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

New Zealand regulatory information:

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

HSNO Approval Number: Group standard HSR002670

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: HSNO - Hazardous Substances and New Organisms

IMDG: International Maritime Dangerous Goods code

 $IATA-DGR: International\ Air\ Transport\ Association-Dangerous\ Goods\ Regulations$

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 2, 9, 11

Page 9 of 9

SDS No.: 153766 V001.2

LOCTITE EA 3463 known as Pipe Repair Kit EPOXY STICK

Date of previous issue: 12.05.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.