

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM) Ramcar Australia & New Zealand

Chemwatch Hazard Alert Code: 4

Chemwatch: 42-7399

Version No: 10.1.1.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 15/12/2020

Print Date: 08/01/2021

L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	BATTERIES, WET, NON- SPILLABLE, electric storage
Chemical formula	Not Applicable
Other means of identification	AMP-Tech, Advantage, Alco, Alco Batteries, Allrounder, Atlas BX, Endurance, Enforcer, Enirgi Power Storage, Evolution, Exide, Exide Batteries, Extreme, Gladiator, Gold Plus, Golf Master, Lightbase, Marshall Batteries, Marshall Power Australia, Positive Batteries, Power Breed, Power Rider, Power Station, Raylite, Rev Plus, Ritar, Sea Master, Silver Plus, Stowaway, Strongbox, Supercharge Batteries, Trojan, Truck Master, V-Max

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Battery. NOTE: Battery presents no chemical hazards during the normal operation provided the recommendations for handling, storage, transport and usage are observed. If the battery is broken and the internal components exposed, health hazards exist which require careful attention. NOTE: The chemical hazards relate to the released contents. Undamaged sealed Lead-acid batteries normally present a low hazard, however damaged batteries may release highly corrosive and toxic contents. Disassembly, abuse or destruction of battery cell may cause violent explosion with scattering of contents. Heating may cause bursting with release of contents.
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	Ramcar Australia & New Zealand
Address	Unit B / 72 Highbrook Drive Auckland 2013 New Zealand
Telephone	+64 9 975 8900
Fax	Not Available
Website	http://www.exidebatteries.co.nz/index.htm , http://marshallbatteries.co.nz , http://www.superchargebatteries.co.nz
Email	whsercw@ramcar.com.au

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+61 2 9186 1132
Other emergency telephone numbers	+64 800 700 112

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Acute Toxicity (Oral) Category 3, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Acute Toxicity (Inhalation) Category 3, Germ cell mutagenicity Category 2, Carcinogenicity Category 2, Reproductive Toxicity Category 1, Lactation Effects, Specific target organ toxicity - single exposure Category 1, Specific target organ toxicity - repeated exposure Category 1, Acute Aquatic Hazard Category 1, Chronic Aquatic Hazard Category 1, Acute Vertebrate Hazard Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1C (inhalation), 6.1C (oral), 6.3A, 8.3A, 6.6B, 6.7B, 6.8A, 6.8C, 6.9A, 9.1A, 9.3A

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H301	Toxic if swallowed.
H315	Causes skin irritation.

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

H318	Causes serious eye damage.
H331	Toxic if inhaled.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H362	May cause harm to breast-fed children.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H431	Very toxic to terrestrial vertebrates.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume.
P263	Avoid contact during pregnancy and while nursing.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.
P321	Specific treatment (see advice on this label).
P330	Rinse mouth.
P391	Collect spillage.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		Sealed container with electrochemical
Not Available		contents typically,
7439-92-1	55-85	<u>lead</u>
1309-60-0	15-40	<u>lead dioxide</u>
Not Available		electrolyte (no fluid/ completely absorbed) as;
7664-93-9	5-30	<u>sulfuric acid</u>
Not Available		case material as;
9003-07-0	<10	<u>polypropylene</u>
9003-56-9		<u>styrene/ butadiene/ acrylonitrile copolymer</u>
Not Available	<5	separator
7440-31-5	<2	<u>tin</u>
7440-70-2	<1	<u>calcium</u>

SECTION 4 First aid measures

Description of first aid measures

Continued...

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to strong acids:

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- ▶ Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- ▶ Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.

INGESTION:

- ▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ **DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.**
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ▶ Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- ▶ Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- ▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- ▶ Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. **DO NOT use neutralising agents or any other additives.** Several litres of saline are required.
- ▶ Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

- ▶ Gastric acids solubilise lead and its salts and lead absorption occurs in the small bowel.
- ▶ Particles of less than 1 µm diameter are substantially absorbed by the alveoli following inhalation.
- ▶ Lead is distributed to the red blood cells and has a half-life of 35 days. It is subsequently redistributed to soft tissue & bone-stores or eliminated. The kidney accounts for 75% of daily lead loss; integumentary and alimentary losses account for the remainder.
- ▶ Neurasthenic symptoms are the most common symptoms of intoxication. Lead toxicity produces a classic motor neuropathy. Acute encephalopathy appears infrequently in adults. Diazepam is the best drug for seizures.
- ▶ Whole-blood lead is the best measure of recent exposure; free erythrocyte protoporphyrin (FEP) provides the best screening for chronic exposure. Obvious clinical symptoms occur in adults when whole-blood lead exceeds 80 µg/dL.
- ▶ British Anti-Lewisite is an effective antidote and enhances faecal and urinary excretion of lead. The onset of action of BAL is about 30 minutes and most of the chelated metal complex is excreted in 4-6 hours, primarily in the bile. Adverse reaction appears in up to 50% of patients given BAL in doses exceeding 5 mg/kg. CaNa2EDTA has also been used alone or in concert with BAL as an antidote. D-penicillamine is the usual oral agent for mobilisation of bone lead; its use in the treatment of lead poisoning remains investigational. 2,3-dimercapto-1-propanesulfonic acid (DMPS) and dimercaptosuccinic acid (DMSA) are water soluble analogues of BAL and their effectiveness is undergoing review. As a rule, stop BAL if lead decreases below 50 µg/dL; stop CaNa2EDTA if blood lead decreases below 40 µg/dL or urinary lead drops below 2 mg/24hrs.

[Ellenhorn & Barceloux: Medical Toxicology]**BIOLOGICAL EXPOSURE INDEX - BEI**

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Lead in blood	30 µg/100 ml	Not Critical	
2. Lead in urine	150 µg/gm creatinine	Not Critical	B
3. Zinc protoporphyrin in blood	250 µg/100 ml erythrocytes OR 100 µg/100 ml blood	After 1 month exposure	B

B: Background levels occur in specimens collected from subjects **NOT** exposed.

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ Water spray or fog.
- ▶ Foam.

Continued...

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically.
-----------------------------	---

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use fire fighting procedures suitable for surrounding area. ▶ Do not approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use. <p>Slight hazard when exposed to heat, flame and oxidisers.</p>
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ May emit corrosive, poisonous fumes. May emit acrid smoke. <p>Decomposition may produce toxic fumes of: sulfur oxides (SO_x) metal oxides</p>

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Secure load if safe to do so. ▶ Bundle/collect recoverable product. ▶ Collect remaining material in containers with covers for disposal.
Major Spills	<p>Remove combustible materials and all ignition sources. Acid spills may be neutralised with soda ash.</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<p>Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area</p> <ul style="list-style-type: none"> ▶ Avoid smoking, naked lights or ignition sources. <p>When handling, DO NOT eat, drink or smoke.</p> <p>Wash hands with soap and water after handling.</p> <ul style="list-style-type: none"> ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	<ul style="list-style-type: none"> ▶ DO NOT store near acids, or oxidising agents ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Store away from incompatible materials.

Conditions for safe storage, including any incompatibilities

Suitable container	Store in original containers.
Storage incompatibility	<p>Protect from accidental short-circuit.</p> <ul style="list-style-type: none"> ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. ▶ Keep dry

Continued...

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

▶ Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	lead	Lead, inorganic dusts and fumes, as Pb	0.05 mg/m ³	Not Available	Not Available	bio-Exposure can also be estimated by biological monitoring. 6.7B-Suspected carcinogen
New Zealand Workplace Exposure Standards (WES)	lead dioxide	Lead, inorganic dusts and fumes, as Pb	0.05 mg/m ³	Not Available	Not Available	bio-Exposure can also be estimated by biological monitoring. 6.7B-Suspected carcinogen
New Zealand Workplace Exposure Standards (WES)	sulfuric acid	Sulphuric acid	0.1 mg/m ³	Not Available	Not Available	6.7A-Confirmed carcinogen
New Zealand Workplace Exposure Standards (WES)	tin	Tin metal	2 mg/m ³	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lead	Lead	0.15 mg/m ³	120 mg/m ³	700 mg/m ³
lead dioxide	Lead dioxide	0.17 mg/m ³	140 mg/m ³	810 mg/m ³
sulfuric acid	Sulfuric acid	Not Available	Not Available	Not Available
polypropylene	Polypropylene	5.2 mg/m ³	58 mg/m ³	350 mg/m ³
tin	Tin	6 mg/m ³	67 mg/m ³	400 mg/m ³

Ingredient	Original IDLH	Revised IDLH
lead	Not Available	Not Available
lead dioxide	100 mg/m ³	Not Available
sulfuric acid	15 mg/m ³	Not Available
polypropylene	Not Available	Not Available
styrene/ butadiene/ acrylonitrile copolymer	Not Available	Not Available
tin	Not Available	Not Available
calcium	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
calcium	C	> 0.1 to ≤ milligrams per cubic meter of air (mg/m ³)

Notes: Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.


MATERIAL DATA

None assigned. Refer to individual constituents.

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p>	
	Type of Contaminant:	Air Speed:
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	
<p>Within each range the appropriate value depends on:</p>		

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

	<p>Lower end of the range</p> <p>1: Room air currents minimal or favourable to capture</p> <p>2: Contaminants of low toxicity or of nuisance value only.</p> <p>3: Intermittent, low production.</p> <p>4: Large hood or large air mass in motion</p>	<p>Upper end of the range</p> <p>1: Disturbing room air currents</p> <p>2: Contaminants of high toxicity</p> <p>3: High production, heavy use</p> <p>4: Small hood-local control only</p>
	<p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	
Personal protection		
Eye and face protection	<p>None under normal operating conditions.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 	
Skin protection	See Hand protection below	
Hands/feet protection	<ul style="list-style-type: none"> ▶ Elbow length PVC gloves <p>Wear safety footwear.</p>	
Body protection	See Other protection below	
Other protection	<p>No special equipment needed when handling small quantities.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> ▶ Overalls. ▶ Barrier cream. ▶ Eyewash unit. 	

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

Material	CPI
NATURAL RUBBER	A
NATURAL+NEOPRENE	A
NEOPRENE	A
NEOPRENE/NATURAL	A
NITRILE	A
PE	A
PVC	A
SARANEX-23	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AE-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AE-AUS P2	-	AE-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AE-AUS / Class 1 P2	-
up to 100 x ES	-	AE-2 P2	AE-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Manufactured article; insoluble in water.		
Physical state	Manufactured	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Continued...

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	74.2 (H2 gas in air)	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	4.1 (H2 gas in air)	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▸ Contact with alkaline material liberates heat · Unstable in the presence of incompatible materials
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.</p> <p>Exposure to high concentrations causes bronchitis and is characterised by the onset of haemorrhagic pulmonary oedema.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.</p>
Ingestion	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Oedema of the epiglottis may produce respiratory distress and possibly, asphyxia. Nausea, vomiting, diarrhoea and a pronounced thirst may occur. More severe exposures may produce a vomitus containing fresh or dark blood and large shreds of mucosa. Shock, with marked hypotension, weak and rapid pulse, shallow respiration and clammy skin may be symptomatic of the exposure. Circulatory collapse may, if left untreated, result in renal failure. Severe cases may show gastric and oesophageal perforation with peritonitis, fever and abdominal rigidity. Stricture of the oesophageal, gastric and pyloric sphincter may occur as within several weeks or may be delayed for years. Death may be rapid and often results from asphyxia, circulatory collapse or aspiration of even minute amounts. Delayed deaths may be due to peritonitis, severe nephritis or pneumonia. Coma and convulsions may be terminal.</p>
Skin Contact	<p>Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.</p>
Eye	<p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possible irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply vascularised and opaque resulting in blindness.</p>
Chronic	<p>Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.</p> <p>The impact of inhaled acidic agents on the respiratory tract depends upon a number of interrelated factors. These include physicochemical characteristics, e.g., gas versus aerosol; particle size (small particles can penetrate deeper into the lung); water solubility (more soluble agents are more likely to be removed in the nose and mouth). Given the general lack of information on the particle size of aerosols involved in occupational exposures to acids, it is difficult to identify their principal deposition site within the respiratory tract. Acid mists containing particles with a diameter of up to a few micrometers will be deposited in both the upper and lower airways. They are irritating to mucous epithelia, they cause dental erosion, and they produce acute effects in the lungs (symptoms and changes in pulmonary function). Asthmatics appear to be at particular risk for pulmonary effects.</p> <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.</p> <p>There is sufficient evidence to establish a causal relationship between human exposure to the material and subsequent developmental toxic effects in the off-spring.</p>

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

	<p>Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.</p> <p>Excessive exposure to lead can affect the blood, the nervous system, heart, endocrine organs and the immune system and the digestive system. The synthesis of haemoglobin is inhibited and can result in anaemia. If left untreated, neuromuscular dysfunction, possible paralysis and encephalopathy (brain tissue damage) may result. Other symptoms of overexposure include joint and muscle pain, weakness of the extensor muscles (frequently the hand and wrist), headache, dizziness, abdominal pain, diarrhoea, constipation, nausea, vomiting, blue line on the gums, insomnia and metallic taste. High body levels produce cerebrospinal pressure, brain damage with stupor leading to coma and, in some cases, death. Early symptoms of lead poisoning ("plumbism") include anorexia and loss of weight, constipation, apathy or irritability, occasional vomiting, fatigue, headache, weakness, and a metallic taste in the mouth. Advanced poisonings are characterised by intermittent vomiting, irritability, nervousness, myalgia of the arms and legs (often with wrist and foot drop). Severe poisonings may produce persistent vomiting, ataxia, stupor or lethargy, visual disturbances progressing to optic neuritis and atrophy, hyper-tension, papilloedema, cranial nerve paralysis, delirium, convulsions and coma. Neurological effects include mental retardation, seizures, cerebral palsy and marked muscular contractions that distort the spine, limbs, hips and sometimes the cranial innervated muscles (dystonia musculorum deformans). Industrial exposure has been associated with irreversible kidney damage.</p>
--	--

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)	TOXICITY	IRRITATION
	Not Available	Not Available
lead	0.01 mg/kg ^[2]	Not Available
	450 mg/kg ^[2]	
	Oral(Rat) LD50 >2000 mg/kg ^[1]	
lead dioxide	Not Available	Not Available
sulfuric acid	=135 mg/kg ^[2]	Eye (rabbit): 1.38 mg SEVERE
	3 mg/kg ^[2]	Eye (rabbit): 5 mg/30sec SEVERE
	Inhalation(Guinea) LC50 0.036 mg/l/8H ^[2]	
	Inhalation(Rat) LC50 0.255 mg/l/2hE ^[2]	
	Oral(Rat) LD50 =2140 mg/kg ^[2]	
polypropylene	Oral(Mouse) LD50 3200 mg/kg ^[2]	Not Available
	Oral(Rat) LD50 >8000 mg/kg ^[2]	
styrene/ butadiene/ acrylonitrile copolymer	Dermal (rabbit) LD50: 5010 mg/kg ^[2]	Not Available
	Oral(Rat) LD50 5010 mg/kg ^[2]	
tin	Oral(Rat) LD50 >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
calcium	Not Available	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

LEAD	WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.
SULFURIC ACID	WARNING: For inhalation exposure <u>ONLY</u> : This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS Occupational exposures to strong inorganic acid mists of sulfuric acid:
POLYPROPYLENE	* For pyrolyzate for poly-alpha-olefins (PAOs): PAOs are highly branched isoparaffinic chemicals produced by oligomerisation of 1-octene, 1-decene, and/or 1-dodecene. The crude polyalphaolefin mixture is then distilled into appropriate product fractions to meet specific viscosity specifications and hydrogenated. Read across data exist for health effects endpoints from the following similar <i>hydrogenated</i> long chain branched alkanes derived from a C8, C10, and/or C12 alpha olefins: <ul style="list-style-type: none"> ▶ Decene homopolymer ▶ Decene/dodecene copolymer ▶ Octene/decene/dodecene copolymer ▶ Dodecene trimer

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

The data for these structural analogs demonstrated no evidence of health effects. In addition, there is evidence in the literature that alkanes with 30 or more carbon atoms are unlikely to be absorbed when administered orally. The physicochemical data suggest that it is unlikely that significant absorption will occur. If a substance of the size and structure of a typical PAO is absorbed, then the principal mechanisms of absorption after oral administration are likely to be passive diffusion and absorption by way of the lymphatic system. The former requires both good lipid solubility and good water solubility as the substance has to partition from an aqueous environment through a lipophilic membrane into another aqueous environment during absorption. Absorption by way of the lymphatics occurs by mechanisms analogous to those that absorb fatty acids and is limited by the size of the molecule. Lipophilicity generally enhances the ability of chemicals to cross biological membranes. Biotransformation by mixed function oxidases often increases the water solubility of a substance; however, existing data suggest that these substances will not undergo oxidation to more hydrophilic metabolites. Finally, a chemical must have an active functional group that can interact chemically or physically with the target cell or receptor upon reaching it; there are no moieties in PAOs that represent a functional group that may have biological activity. The water solubilities of a C10 dimer PAO and a C12 trimer PAO were determined to be <1 ppb and <1 ppt respectively. The partition coefficient for a C12 trimer PAO was determined to be log Kow of >7. Given the very low water solubility it is extremely unlikely that PAOs will be absorbed by passive diffusion following oral administration, and the size of the molecules suggest that the extent of lymphatic absorption is likely to be very low. Although PAOs are relatively large lipophilic compounds, and molecular size may be a critical limiting determinant for absorption, there is some evidence that these substances are absorbed. However, the lack of observed toxicity in the studies with PAOs suggests that these products are absorbed poorly, if at all. Furthermore, a review of the literature regarding the absorption and metabolism of long chain alkanes indicates that alkanes with 30+ carbon atoms are unlikely to be absorbed. For example the absorption of squalane, an analogous C30 product, administered orally to male CD rats was examined - essentially all of the squalane was recovered unchanged in the faeces. At the same time, the hydrophobic properties of PAOs suggest that, should they be absorbed, they would undergo limited distribution in the aqueous systemic circulation and reach potential target organs in limited concentrations.

In addition to the general considerations discussed above, the low volatility of PAOs indicates that, under normal conditions of use or transportation, exposure by the inhalation route is unlikely. In particular, the high viscosity of these substances suggests that it would be difficult to generate a high concentration of respirable particles in the air.

Acute toxicity: PAOs (decene/dodecene copolymer, octene/decene/dodecene homo-polymer, and dodecene trimer) have been adequately tested for acute oral toxicity. There were no deaths when the test materials were administered at doses of 5,000 mg/kg (decene/dodecene copolymer and dodecene trimer) and at 2,000 mg/kg (octene/decene/dodecene copolymer) in rats. Overall, the acute oral LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.

PAOs (decene/dodecene copolymer, octene/decene/dodecene copolymer, and dodecene trimer) have been tested for acute dermal toxicity. No mortality was observed for any substance when administered at the limit dose of 2000 or 5000 mg/kg. Overall, the acute dermal LD50 for these substances was greater than the 2000 mg/kg limit dose, indicating a relatively low order of toxicity.

1-Decene, homopolymer, is absorbed (unexpectedly for a high molecular weight polymer) to a moderate degree in rat skin and is eliminated slowly

PAOs (decene homopolymer, decene/dodecene copolymer, and decene trimer) have been tested for acute inhalation toxicity. Rats were exposed to aerosols of the substances at nominal atmospheric concentrations of 2.5, 5.0, and 5.06 mg/L, respectively, for four hours. These levels were the maximum attainable concentrations under the conditions of the tests, due to the low volatility and high viscosity of the test material. No mortality was noted, and all animals fully recovered following depuration. The lack of mortality at concentrations at or above the limit dose of 2.0 mg/L indicates a relatively low order of toxicity for these substances.

Repeat dose toxicity: Eight repeated-dose toxicity studies using two different animal species, rats and mice, and oral and dermal routes of administration have been conducted with three structural analogs. These data suggest that the structural analogs exhibit a low order of toxicity following repeated applications, due to their similarity in chemical structures and physicochemical properties.

One 28-day oral toxicity study in rats, one 90-day dermal and two 90-day dietary studies in rats, and a dermal carcinogenicity study in mice exist for decene homopolymer. A rat oral combined reproductive toxicity and 91-day systemic toxicity study was also conducted with decene homopolymer. In addition, 28-day rat oral toxicity studies exist for two structurally analogous substances (dodecene trimer and octene/decene/dodecene copolymer); and a 90-day rat dermal toxicity study exists for octene/decene/dodecene copolymer. Results from these studies show a low order of repeated dose toxicity. The dermal NOAEL for systemic toxicity studies was equal to or greater than 2000 mg/kg/day.

The oral NOAEL for 1-decene homopolymer is between 5,000 and 20,000 mg/kg/day in Sprague-Dawley rats.

Rats exposed repeatedly by dermal exposure at doses of 2000 mg/kg decene/dodecene copolymer showed increased incidences of hyperplasia of the sebaceous glands, hyperplasia/hyperkeratosis of the epidermis and dermal inflammation. These symptoms generally subsided within 2 weeks. Males showed decreased body weight gain and altered serum chemistry.

In a 90-day feeding study rats receiving 20000 ppm of 1-decene, homopolymer, hydrogenated did not exhibit any clinical signs of systemic toxicity. Marginal effects on clinical chemistry (glucose and ALT in males; sodium, phosphorus and calcium in females) were seen.

Reproductive toxicity: Data are available for decene homopolymer. Results from these studies show a low order of reproductive/developmental toxicity. The NOAEL for reproductive toxicity was 1000 mg/kg/day, the highest concentration tested. The lack of effects on fertility in this study or effects on reproductive organs in this or other subchronic studies with closely related chemicals indicates that PAOs are unlikely to exert effects on reproduction.

Developmental toxicity: Decene homopolymer (with 10 ppm of an antioxidant) was administered once daily on gestation days 0-19 via dermal application to presumed-pregnant rats at doses of 0, 800, and 2000 mg/kg/day. Dermal administration of the test material did not adversely affect parameters of reproductive performance during gestation, nor did it adversely affect *in utero* survival and development of the offspring. The NOAEL in this study for developmental parameters was 2000 mg/kg/day.

Genotoxicity: Information for the following PAOs (decene homopolymer, octene/decene/dodecene copolymer, dodecene trimer; and decene/dodecene copolymer [prepared from 10% C12 and 90% C10 alpha olefins; approx. 33% trimer and 51% tetramer, 16% pentamer and higher]) is available. Either bacterial or mammalian gene mutation assays, *in vitro* chromosomal aberration assays, or *in vivo* chromosomal aberration assays have been conducted for these substances. Neither mutagenicity nor clastogenicity were exhibited by any of these substances in the referenced *in vivo* or *in vitro* tests, with or without metabolic activation.

Carcinogenicity: While alpha-olefin polymers have similar properties to mineral oils, they do not contain polycyclic aromatic hydrocarbons, or other known possible carcinogens.

Decene homopolymer produced no treatment-related tumors in C3H mice treated with a 50 ul/application twice weekly for 104 weeks. In addition, survival (56%) was greater than in any other group, including the untreated control.

STYRENE/ BUTADIENE/ ACRYLONITRILE COPOLYMER	Ultrafine particles (UFPs) may be produced at lower temperatures during the 3D printing process Concerns have been raised regarding airborne UFP concentrations generated while printing with ABS, as UFPs have been linked with adverse health effects
CALCIUM	The solid may react violently on contact with wet skin tissue, i.e. eyes, mouth, causing chemical and thermal burns. The acute effects include burns, ulceration, or tissue death, severe eye damage (corneal burns or opacification), and probable blindness. Inhalation of dust or fumes (especially from a fire involving calcium) will cause shortness of breath, nausea, headache, nose and respiratory tract irritation and in extreme, pneumonitis
Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM) & TIN & CALCIUM	No significant acute toxicological data identified in literature search.
SULFURIC ACID & CALCIUM	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

POLYPROPYLENE & STYRENE/ BUTADIENE/ ACRYLONITRILE COPOLYMER

The substance is classified by IARC as Group 3:
NOT classifiable as to its carcinogenicity to humans.
 Evidence of carcinogenicity may be inadequate or limited in animal testing.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✓
Mutagenicity	✓	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
lead	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.0079mg/L	2
	EC50	48	Crustacea	0.029mg/L	2
	EC50	72	Algae or other aquatic plants	0.0205mg/L	2
	BCF	864	Not Available	-24.19-24.23mg/L	4
NOEC	672	Fish	0.00003-mg/L	4	
lead dioxide	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC	264	Algae or other aquatic plants	0.0091mg/L	2
sulfuric acid	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>16-<28mg/L	2
	EC50	48	Crustacea	=42.5mg/L	1
	EC50	72	Algae or other aquatic plants	2.56mg/L	2
NOEC	Not Available	Crustacea	0.15mg/L	2	
polypropylene	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
styrene/ butadiene/ acrylonitrile copolymer	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
tin	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>0.0124mg/L	2
	EC50	72	Algae or other aquatic plants	>0.0192mg/L	2
	BCFD	1224	Not Available	<0.00004-0.00034mg/L	4
NOEC	168	Crustacea	<0.005mg/L	2	
calcium	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48	Crustacea	49.1mg/L	2
	BCF	6480	Not Available	0.031-mg/L	4
	EC100	48	Crustacea	75mg/L	2
NOEC	336	Crustacea	32mg/L	2	

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
polypropylene	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
polypropylene	LOW (LogKOW = 1.6783)

Mobility in soil

Ingredient	Mobility
polypropylene	LOW (KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. Otherwise: <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.
-------------------------------------	--



Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.
The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.
Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	2R

Land transport (UN)

UN number	2800				
UN proper shipping name	BATTERIES, WET, NON- SPILLABLE, electric storage				
Transport hazard class(es)	<table border="1"> <tr> <td>Class</td> <td>8</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table>	Class	8	Subrisk	Not Applicable
Class	8				
Subrisk	Not Applicable				
Packing group	Not Applicable				
Environmental hazard	Environmentally hazardous				
Special precautions for user	<table border="1"> <tr> <td>Special provisions</td> <td>238</td> </tr> <tr> <td>Limited quantity</td> <td>1 L</td> </tr> </table>	Special provisions	238	Limited quantity	1 L
Special provisions	238				
Limited quantity	1 L				

Air transport (ICAO-IATA / DGR)

UN number	2800				
UN proper shipping name	Batteries, wet, non-spillable electric storage				
Transport hazard class(es)	<table border="1"> <tr> <td>ICAO/IATA Class</td> <td>8</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> </table>	ICAO/IATA Class	8	ICAO / IATA Subrisk	Not Applicable
ICAO/IATA Class	8				
ICAO / IATA Subrisk	Not Applicable				

Valve Regulated Lead-Acid Battery (VRLA) Absorbed Electrolyte Battery (AGM)

	ERG Code	8L
Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A48 A67 A164 A183
	Cargo Only Packing Instructions	872
	Cargo Only Maximum Qty / Pack	No Limit
	Passenger and Cargo Packing Instructions	872
	Passenger and Cargo Maximum Qty / Pack	No Limit
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	2800	
UN proper shipping name	BATTERIES, WET, NON-SPILLABLE electric storage	
Transport hazard class(es)	IMDG Class	8
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-A , S-B
	Special provisions	238
	Limited Quantities	1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002536	Gas Under Pressure Mixtures (Toxic [6.1]) Group Standard 2017
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2017
HSR002592	Industrial and Institutional Cleaning Products (Toxic [6.1 + 6.7]) Group Standard 2017
HSR002613	Metal Industry Products (Toxic [6.1 + 6.7]) Group Standard 2017
HSR002626	N.O.S. (Toxic [6.1, 6.7], Combustible) Group Standard 2017
HSR002671	Surface Coatings and Colourants (Toxic [6.1 + 6.7]) Group Standard 2017
HSR002504	Additives, Process Chemicals and Raw Materials (Toxic [6.1 + 6.7]) Group Standard 2017
HSR100425	Pharmaceutical Active Ingredients Group Standard 2017
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2017
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2017
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2017
HSR002625	N.O.S. (Toxic [6.1, 6.7]) Group Standard 2017

lead is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

lead dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans
 New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)
 New Zealand Workplace Exposure Standards (WES)

sulfuric acid is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans
 New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)
 New Zealand Workplace Exposure Standards (WES)

polypropylene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
 New Zealand Inventory of Chemicals (NZIoC)

styrene/ butadiene/ acrylonitrile copolymer is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
 New Zealand Inventory of Chemicals (NZIoC)

tin is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)
 New Zealand Workplace Exposure Standards (WES)

calcium is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
 New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
 New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Compliance Certificate)	Quantity (Compliance Certificate - Farms >4 ha)
6.1C	1000 kg or 1000 L	3500 kg or 3500 L

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.1C	120	1	3	

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (lead; lead dioxide; sulfuric acid; polypropylene; styrene/ butadiene/ acrylonitrile copolymer; tin; calcium)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polypropylene; styrene/ butadiene/ acrylonitrile copolymer)
Japan - ENCS	No (lead; tin; calcium)
Korea - KECI	Yes

National Inventory	Status
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes

Legend: Yes = All CAS declared ingredients are on the inventory
No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	15/12/2020
Initial Date	26/08/2014

SDS Version Summary

Version	Issue Date	Sections Updated
8.1.1.1	18/11/2020	Ingredients
10.1.1.1	15/12/2020	Classification, Ingredients

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.