

1. Identification of Substance & Company

Product

Product name	Maxlife Button Cell Lithium
Product code	to be advised
HSNO approval	exempt - manufactured article
Approval description	exempt - manufactured article
UN number	NA
Proper Shipping Name	NA
Packaging group	NA
Hazchem code	NA
Uses	Battery

Company Details

Company	P.K. Global Limited
Address	136Motu Road RD1 Kumeu Auckland 0891 New Zealand
Telephone	0064 9 412 5136
Fax	0064 9 412 5135

Emergency Telephone Number: 0800-764 766

2. Hazard Identification

Approval

Manufactured article: Batteries are considered to be manufactured articles and are not, therefore, covered by the HSNO Act. Under normal circumstances, a battery is sealed and the substance is not expected to be released. The following classification and hazards are associated with the contents of an open battery.

Classes	Hazard Statements
4.3A	In contact with water releases flammable gases which may ignite spontaneously.
6.1D (oral)	Harmful if swallowed
6.1D (inhalation)	Harmful if inhaled.
8.2C	Causes severe skin burns and eye damage.
8.3A	Causes serious eye damage.
6.5B	May cause an allergic skin reaction.
6.6A	May cause genetic defects.
6.8A	May damage fertility or the unborn child.
6.8C	May cause harm to breast-fed children.
6.9A	Causes damage to organs through prolonged or repeated exposure
9.1A	Very toxic to aquatic life.
9.3C	Harmful to terrestrial vertebrates.

SYMBOLS

DANGER



Other Classifications

Swallowing an intact battery may lead to serious injury or death within 2 hours. Battery may cause chemical burns and damage to the gastrointestinal tract if swallowed.

If intact battery is swallowed, seek medical attention immediately.

If batteries are placed in a fire, they may rupture and the contents may intensify the fire.

Precautionary Statements – these apply to the contents of an opened battery.

Keep out of reach of children.
Do not breathe dust/vapours.
Wash hands thoroughly after handling.
Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Handle under inert gas. Protect from moisture.
Wear protective gloves/protective clothing/eye protection/face protection.
Contaminated work clothing should not be allowed out of the workplace.
Obtain special instructions before handling contents.
Do not handle until all safety precautions have been read and understood.
Avoid contact during pregnancy/while nursing.
Do not eat, drink or smoke when using this product.
IF exposed or concerned: Get medical advice/ attention.
In case of fire: Use foam extinguisher for extinction

Avoid release to the environment.
Collect spillage.

Further precautionary statements can be found in Section 4 – First Aid.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Concentration
graphite	7782-42-5	1-2%
1,2-dimethoxyethane	110-71-4	3-4%
lithium or lithium alloy	7439-93-2	1-3%
lithium perchlorate	7791-03-9	1-2%
Nickel	7440-02-0	20-30%
Copper	7440-50-8	3-4%
Manganese/Manganese dioxide	1313-13-9	30-40%
propylene carbonate	108-32-7	3-4%
non hazardous ingredients	proprietary	balance

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid**General Information**

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Recommended first aid facilities

Ready access to running water is required. Accessible eyewash is required.

Exposure**Swallowed**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Contact a doctor immediately.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

Inhaled

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards:	Batteries may present a hazard if exposed to a fire. Batteries can rupture in a fire and release contents as toxic fumes or vapours. Lithium can react with water and release hydrogen which adds to the fire risk. Hydrogen gas is explosive.
Suitable extinguishing substances:	Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or alcohol resistant foam. Keep intact batteries cool if exposed to a fire to prevent rupture.
Unsuitable extinguishing substances:	Unknown.
Products of combustion:	Batteries may emit toxic fumes and vapours in a fire.
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	NA

6. Accidental Release Measures

Containment	There is no current legal requirement for containment of this product. It is a manufactured article.
Emergency procedures for release of contents of a battery	In the event that a battery is damaged and the content is released: Wear protective equipment to prevent skin, eye and respiratory exposure. (see section 8 for details). Contain leakage using sand, earth or vermiculite. Collect and seal in properly labelled containers for disposal.
Emergency procedures (intact batteries)	In the event of spillage of a large number of batteries (>100kg) alert the fire brigade to location and give brief description of hazard. Stop the source of the leak, if safe to do so. Prevent by whatever means possible any batteries from entering drains, sewers, or water courses. (If this occurs contact your regional council immediately).
Disposal	Collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	For content of open batteries: Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. For batteries: Ensure that no damage occurs to the batteries to prevent leakage of the content.

7. Storage & Handling

Storage	Store batteries in a cool, dry, well ventilation area. Keep away from heat, fire, sunlight and ignition sources. Store batteries in their packaging. Unpacked batteries may short circuit and generate heat. Keep away from children. Battery cells are small enough to be swallowed. If this happens contact a doctor immediately.
Handling	Handle batteries with care. Do not recharge batteries, as this may cause leakage or rupture of the battery. Do not solder or weld onto the battery. Do not mix with used, or other battery types. If handling the contents of an open battery: Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapours/dusts.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

During normal use of a battery release of the contents of the battery does not occur.

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this contents of the battery. There is a general limit of 10mg/m³ for dusts and mists when limits have not otherwise been established.

NZ Workplace Exposure Stds (2013)	Ingredient	WES-TWA	WES-STEL
	Manganese Dioxide	1mg/m ³	data unavailable
	Graphite	3mg/m ³	data unavailable
	Lithium (Lithium Hydroxide)	data unavailable	1mg/m ³
	Copper	0.2mg/m ³ (fumes), 1mg/m ³ (dusts/mists)	data unavailable
	Nickel	1mg/m ³	data unavailable

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety in Employment Act 1992 (HSE). Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



If handling the contents of an open battery, Protect eyes with goggles, safety glasses or full face mask. Avoid wearing contact lenses.

Skin



If handling the contents of an open battery, avoid skin contact. Wear overalls, rubber boots and impervious gloves. Nitrile or PVC gloves are recommended. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking.

Respiratory

A respirator when airborne concentrations approach the WES (section 8). Use a respirator with a particulate filter. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance	metal button cell containing electrolyte solution
Odour	intact battery has no odour
pH	no data
Vapour pressure	no data
Viscosity	no data
Boiling point	no data
Volatile materials	no data
Freezing / melting point	no data
Solubility	partly soluble in water
Specific gravity / density	2.84
Flash point	non flammable
Danger of explosion	no data
Auto-ignition temperature	no data
Upper & lower flammable limits	no data
Corrosiveness	contents of the battery is corrosive to skin and eyes.

10. Stability & Reactivity

Stability	Stable at room temperature and pressure. Stable during normal use.
Conditions to be avoided	Keep from extreme heat and open flames. Do not puncture, crush or incinerate. Do not immerse in water. Prevent short circuits. Do not attempt to recharge this battery.
Incompatible groups	Content of the battery: water, oxidising agents.
Substance Specific Incompatibility	none known
Hazardous decomposition products	Manganese oxides, carbon dioxide, carbon monoxide. Lithium oxides, hydrogen gas.
Hazardous reactions	none known

11. Toxicological Information**Summary**

During normal use the battery are not considered harmful/toxic.

The following summary is for the contents of the battery.

IF SWALLOWED: Can cause burning and permanent damage to the mouth and throat.

IF IN EYES: cause permanent eye damage.

IF ON SKIN: causes burns to the skin. May also cause allergic dermatitis (copper, nickel)

IF INHALED: if vapours are inhaled, these can cause respiratory irritation.

CHRONIC TOXICITY: prolonged or repeated contact with the contents of the battery may cause long term toxicity. Inhalation may impair brain function and show some developmental toxicity, i.e. it may affect foetus) and toxicity via breastmilk. (Manganese dioxide).

Supporting Data

Acute	Oral	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral) for the mixture is between 2000 and 5,000 mg/kg. Data considered includes: Manganese Dioxide 3480mg/kg, copper compounds: 15mg (Cu)/kg (guinea pig). 1,2-dimethoxyethane: 3200mg/kg (mouse).
	Dermal Inhaled	No evidence of dermal toxicity. Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is between 2 and 5 mg/L (dust/mist) ppm. Data considered includes: Manganese Dioxide LCL0: 0.5mg/L (dust/mist).
Chronic	Eye Skin	The mixture is considered to be corrosive to the eye. The mixture is considered to be corrosive to the skin.
	Sensitisation	Nickel metal and nickel compounds present may be considered respiratory and skin sensitisers. Copper metal and copper compounds are also classed 6.5B.
	Mutagenicity	Copper is classed by EPA as 6.6A – known mutagen.
	Carcinogenicity	Nickel alloy is also considered a carcinogen 6.7B.
	Reproductive / Developmental	The mixture is considered to be a reproductive or developmental toxicant, because Manganese dioxide is known or suspected to have an effect on or via lactation. Manganese dioxide dust has also been shown to affect offspring (developmental toxicity)
	Systemic	The mixture is considered to be a known or presumed target organ toxicant, because manganese dioxide is known or presumed to be a target organ toxicant. This product may affect the brain.
	Aggravation of existing conditions	None known.

12. Ecological Data**Summary**

An intact battery is not considered harmful to the environment. However is exposed to the elements the housing may break down and release the contents of the battery. The contents is considered ecotoxic in the aquatic environment. Do not allow contents to reach waterways.

Supporting Data – for the contents of the battery

Aquatic	Using EC ₅₀ 's for the contents of the battery: the calculated EC ₅₀ for the mixture is < 1 mg/L. Data considered includes: Copper compounds; 0.212 mg/L (96hr, Atherinops affinis (Topsmelt)), 0.44 mg/L (48hr, Artemia salina (Brine shrimp)), 0.0127 mg/L (72hr, Chlorella protothecoides (Green algae)), nickel: 0.46mg/L (72hr, Acartia tonsa Calanoid copepod), 8mg/L (96hr, Lepomis gibbosus), 2.48mg/L (96hr, Rockbass). Lithium: 28mg/l (Ptychocheilus lucius (Colorado pike minnow))
Bioaccumulation	No data
Degradability	No data
Soil	EPA has not classified any of the ingredients as ecotoxic in the soil environment.
Terrestrial vertebrate	The contents of the battery may be harmful towards terrestrial vertebrates. See acute toxicity above.
Terrestrial invertebrate	There is no evidence of toxicity towards terrestrial invertebrates.
Biocidal	no data
Environmental effect levels	No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Rinse containers with water before disposal. Preferably re-cycle container, otherwise send to landfill or similar.

14. Transport Information**LAND TRANSPORT:**

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

UN number:	3090	Proper shipping name:	LITHIUM METAL BATTERIES
Class(es)	9 (Miscellaneous dangerous substances and articles)	Packing group:	III
Precautions:	NA	Hazchem code:	4W

AIR TRANSPORT:

UN number:	3090	Proper shipping name:	LITHIUM METAL BATTERIES
Class(es)	9 (Miscellaneous dangerous substances and articles)	Packing group:	III
Precautions:	NA	ERG Guide No	138

MARINE TRANSPORT:

UN number:	3090	Proper shipping name:	LITHIUM METAL BATTERIES
Class(es)	9 (Miscellaneous dangerous substances and articles)	Packing group:	III
Precautions:	NA	EmS	F-A, S-I

15. Regulatory Information

Batteries are considered to be manufactured articles and are not, therefore, covered by the HSNO Act. Although they may contain hazardous substances, the item has an end use function wholly dependent on its shape and design, which does not involve the intentional release of any hazardous component. (from EPA New Zealand)

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information**Abbreviations**

Approval Code	Approval: exempt - manufactured article Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (New Zealand)
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL	Lower Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
NZIoC	New Zealand Inventory of Chemicals
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UEL	Upper Explosive Limit
UN Number	United Nations Number
WES	Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).
Controls	EPA notices, www.epa.govt.nz , Health and Safety at Work (Hazardous Substances) Regulations 2017, www.legislation.govt.nz
WES	The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz .
Other References:	EU ECHA, ingredients SDS's, ChemIDplus

Review

Date	Reason for review
March 2015	Not applicable – new SDS
February 2020	5 yearly update

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

