



# TECHNICAL DATA SHEET

## CRC NF 5-56 Multi-Purpose



**CRC NF 5-56 Multi-Purpose** is a multi-purpose service spray that penetrates, lubricates and prevents corrosion. It forms a thin film that lubricates moving parts for smooth action and silences annoying squeaks.

CRC NF 5-56 Multi-Purpose has superior penetrating power that loosens rusted parts and displaces water from wet equipment.

CRC NF 5-56 Multi-Purpose is safe for metals and alloys, most painted surfaces, coatings, plastics and rubbers. It is ideal for situations and environments where flammable vapours may ignite and cause a fire.

**Item Code: 1754519**

**Pack Size: 400g Aerosol**

## Features and Benefits

- **Advanced lubrication for smooth action:** Silences annoying squeaks & squeals
- **Stops and attacks rust:** Protective film for ongoing protection against corrosion
- **Penetrates quickly:** Breaks away rust & corrosion, frees components bonded by dirt & scale
- **Ideal for preventative maintenance programs:** To increase the life expectancy of mechanical equipment
- **Displaces moisture to help start wet engines**
- **Eliminates the need for many disassembly operations**
- **Cleans grease and tar off painted surfaces**
- **Ideal for mining and areas with low ventilation**

## Applications

Suitable for tools & machinery, loosening rusted parts, squeaky hinges, starting wet engines, displacing water from wet equipment & more.

## Typical Properties and Characteristics

Flash Point	None
Boiling Point	70°C
Odour	Mild solvent odour
Appearance	Amber liquid
Solubility	Insoluble in water
% Volatile	70%

Vapour Density	> 1
Specific Gravity	1
Flammability	Non-flammable
Propellant	Carbon dioxide
Working Temperature Range	-10°C to 150°C



TOGETHER, WE GET IT DONE.™

[www.crcindustries.com.au](http://www.crcindustries.com.au)



## Directions

1. Hold the can 30cm from the surface and spray liberally.
2. For greater penetration, leave to soak in before working on the part.
3. Wipe away excess fluid with a clean cloth.
4. For starting flooded engines, spray all electrics and leads liberally.

**Note:** When cleaning surfaces, test a small area first for colour fastness.

## Special Precautions

### General:

Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Dispose of contents/container in accordance with relevant regulations.

Refer to **Safety Data Sheet** for more details.

## Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

## Contact Information

**CRC Industries (Aust) Pty Ltd**  
9 Gladstone Road, Castle Hill  
NSW 2154, Australia

[www.crcindustries.com.au](http://www.crcindustries.com.au)  
PH: 1800 224 227  
Email: [info.au@crcind.com](mailto:info.au@crcind.com)

**Disclaimer:** All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

*Technical Data Sheet Version 06/2026*

