

CRC 3360 Chain And Wire Lubricant (Aerosol) CRC Industries (CRC Industries New Zealand)

Chemwatch: 4828-4 Version No: 7.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 4

Issue Date: **10/12/2021**Print Date: **17/10/2024**S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	CRC 3360 Chain And Wire Lubricant (Aerosol)
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Details of the manufacturer or supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	10 Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	+64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	- No EMAL ID NEEDED for NZ - JACK	

Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Aerosols, Hazard Category 1, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.1E (aspiration), 6.4A, 6.9B (narcotic effects), 9.1B

Label elements

Hazard pictogram(s)









Signal word

Danger

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271	Use only outdoors or in a well-ventilated area.	

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331	Do NOT induce vomiting.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	

Precautionary statement(s) Storage

P405	Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
63748-98-1	30-60	mineral oil
Not Available		isohexane, as
107-83-5	10-30	2-methylpentane
Not Available	1-10	performance additives (proprietary)
68476-85-7.	10-30	hydrocarbon propellant
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

Eye	Contact
-----	---------

If aerosols come in contact with the eyes:

- ▶ Immediately hold the eyelids apart and flush the eye with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.

	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may

Advice for firefighters

Advice for inteligities	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Moderate explosion hazard when exposed to heat or flame. WARNING: In use may form flammable/ explosive vapour-air mixtures. Combustion products include: carbon dioxide (CO2)

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Slippery when spilt. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- Todautiono foi caro nana	9
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can Store in original containers in approved flammable liquid storage area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 ▶ Aerosol dispenser. ▶ Check that containers are clearly labelled.
Storage incompatibility	► Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	mineral oil	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	hydrocarbon propellant	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
mineral oil	2,500 mg/m3	Not Available
2-methylpentane	Not Available	Not Available
hydrocarbon propellant	Not Available	Not Available

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
2-methylpentane	Е	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.			
Individual protection measures, such as personal protective equipment				
Eye and face protection	 No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: Safety glasses with side shields. NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them. 			
Skin protection	See Hand protection below			
Hands/feet protection	 No special equipment needed when handling small quantities. OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear. 			
Body protection	See Other protection below			
Other protection	No special equipment needed when handling small quantities. OTHERWISE: Overalls. Skin cleansing cream. Eyewash unit.			

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS	-	AX-PAPR-AUS / Class 1
up to 50 x ES	-	AX-AUS / Class 1	-
up to 100 x ES	-	AX-2	AX-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Straw coloured viscous highly flammable liquid aerosol; not miscible with water. Supplied as an aerosol pack. Contents under PRESSURE . Contains highly flammable hydrocarbon propellant.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	-81 (propellant)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

-	
Inhaled	Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Accidental ingestion of the material may be damaging to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.
Skin Contact	Spray mist may produce discomfort The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material

Eye	Although the liquid is not thought to be an irritant (as classified b	y EC Directives),	direct contact with the eye may produce
Chronic	transient discomfort characterised by tearing or conjunctival redr Main route of exposure to the gas in the workplace is by inhalatic Substance accumulation, in the human body, may occur and ma occupational exposure. Oil may contact the skin or be inhaled. Extended exposure can le face and warts on the soles of the feet. Constant or exposure over long periods to mixed hydrocarbons of disturbance, weight loss and anaemia, and reduced liver and kid and redness of the skin.	on. y cause some co ead to eczema, ir may produce stup	oncern following repeated or long-term Inflammation of hair follicles, pigmentation of the por with dizziness, weakness and visual
CRC 3360 Chain And Wire	TOXICITY	IRRITATION	
Lubricant (Aerosol)	Not Available	Not Available	
	TOXICITY	IRRITATION	
mineral oil	Not Available	Not Available	
	TOXICITY	IRRITATION	
2-methylpentane	Oral (Rat) LD50: ~15.84 mg/kg ^[1]	Not Available	
	TOXICITY	IRRITATION	
hydrocarbon propellant	Inhalation (Rat) LC50: 658 mg/l4h ^[2]	Not Available	
Legend:	Value obtained from Europe ECHA Registered Substances - A Unless otherwise specified data extracted from RTECS - Regist		
Legend:	· · · · · · · · · · · · · · · · · · ·	related from both elated to the seven esirable componed to the degree of essing will have so degree of processe oils is inversellevels of undesirancer-causing and and mildly refined to oils, the highly and very low mammative results, suppon-bioavailable during the colon of the	in process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; ssing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and doils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack use to their molecular size.
	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate base Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negation biologically active components or the components are largely no	related from both elated to the seven esirable componed to the degree of essing will have so degree of processe oils is inversellevels of undesirancer-causing and and mildly refined to oils, the highly and very low mammative results, suppon-bioavailable during the colon of the	in process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; ssing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and doils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack use to their molecular size.
MINERAL OIL HYDROCARBON	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate base Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negation biologically active components or the components are largely no Toxicity testing has consistently shown that lubricating base oils	related from both elated to the seven esirable componed to the degree of essing will have seed degree of processe oils is inversely levels of undesirancer-causing and mildly refined to oils, the highly and very low mammative results, supports of the colon of the co	in process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; ssing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and doils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack use to their molecular size.
HYDROCARBON PROPELLANT 2-METHYLPENTANE & HYDROCARBON	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate bas Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negation biologically active components or the components are largely no Toxicity testing has consistently shown that lubricating base oils inhalation of the gas No significant acute toxicological data identified in literature sear	related from both elated to the seven esirable componed to the degree of essing will have seed degree of processe oils is inversely levels of undesirancer-causing and mildly refined to oils, the highly and very low mammative results, supports of the colon of the co	in process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; ssing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and doils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack use to their molecular size.
HYDROCARBON PROPELLANT 2-METHYLPENTANE & HYDROCARBON PROPELLANT	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate base Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negation biologically active components or the components are largely not Toxicity testing has consistently shown that lubricating base oils inhalation of the gas No significant acute toxicological data identified in literature sear	related from both elated to the seven esirable componed to the degree of essing will have so degree of processe oils is inversel levels of undesirancer-causing and mildly refined to distribution of the collection of the collecti	n process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; ssing the oil receives. y related to the degree of processing, able components, have the largest variation of d mutation-causing activities. Highly and d oils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack the to their molecular size.
HYDROCARBON PROPELLANT 2-METHYLPENTANE & HYDROCARBON PROPELLANT Acute Toxicity	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate base Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negation biologically active components or the components are largely not accomponent to the gas No significant acute toxicological data identified in literature sear.	related from both elated to the seven esirable component to the degree of processes oils is inversellevels of undesiral under causing and and mildly refined to the highly a divery low mammart with the results, supported to the collection of the c	n process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; sasing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and d oils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack are to their molecular size. exicities.
HYDROCARBON PROPELLANT 2-METHYLPENTANE & HYDROCARBON PROPELLANT Acute Toxicity Skin Irritation/Corrosion Serious Eye	Unless otherwise specified data extracted from RTECS - Regist The materials included in the Lubricating Base Oils category are The potential toxicity of a specific distillate base oil is inversely reundergone, since: • The adverse effects of these materials are associated with und • The levels of the undesirable components are inversely related • Distillate base oils receiving the same degree or extent of proce • The potential toxicity of residual base oils is independent of the • The reproductive and developmental toxicity of the distillate base Unrefined & mildly refined distillate base oils contain the highest hydrocarbon molecules and have shown the highest potential caseverely refined distillate base oils are produced from unrefined components. In comparison to unrefined and mildly refined base smaller range of hydrocarbon molecules and have demonstrated mutation-causing and cancer-causing potential has shown negate biologically active components or the components are largely notoxicity testing has consistently shown that lubricating base oils inhalation of the gas No significant acute toxicological data identified in literature sear inhalation of the gas ** Cai**	related from both elated to the seven esirable componed to the degree of processes oils is inversellevels of undesiral and mildly refined to the highly and twee results, the highly and twee results, and the results of undesiral to the highly and twee results, and the results of the results of the results of the results. The results of	n process and physical-chemical perspectives; erity or extent of processing the oil has ents, and processing; similar toxicities; sasing the oil receives. y related to the degree of processing. able components, have the largest variation of d mutation-causing activities. Highly and d oils by removing or transforming undesirable and severely refined distillate base oils have a alian toxicity. Testing of residual oils for orting the belief that these materials lack are to their molecular size. exicities.

Legend: X − Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

CRC 3360 Chain And Wire	Endpoint	Test Duration (hr)	Species	Value	Source
Lubricant (Aerosol)	Not Available	Not Available	Not Available	Not Available	Not Available

	Endpoint	Test Duration (hr)	Species		Source
mineral oil	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
2-methylpentane	EC50(ECx)	96h	Algae or other aquatic plants	4.321mg/l	2
	EC50	96h	Algae or other aquatic plants	4.321mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
harden on the second last	LC50	96h	Fish	24.11mg/l	2
hydrocarbon propellant	EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
	EC50	96h	Algae or other aquatic plants	7.71mg/l	2
Legend:	Extracted from	1. IUCLID Toxicity Data 2. Europe ECHA	Registered Substances - Ecotoxicological	I Information - Aqua	atic Toxicity
	4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -				

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-methylpentane	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2-methylpentane	LOW (LogKOW = 3.2145)

Mobility in soil

Ingredient	Mobility
2-methylpentane	LOW (Log KOC = 124.9)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- ▶ DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required



Marine Pollutant



HAZCHEM	Not Applicable
---------	----------------

Land transport (UN)

14.1. UN number or ID number	1950			
14.2. UN proper shipping name	AEROSOLS	AEROSOLS		
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.1 Not Applicable		
14.4. Packing group	Not Applicable	Not Applicable		
14.5. Environmental hazard	Environmentally hazaı	rdous		
14.6. Special precautions for user	Special provisions 63; 190; 277; 327; 344; 381 Limited quantity 1000ml			

Air transport (ICAO-IATA / DGR)

14.1. UN number	1950		
4.2. UN proper shipping name	Aerosols, flammable		
	ICAO/IATA Class	ICAO/IATA Class 2.1	
3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
0.000(00)	ERG Code	10L	
.4. Packing group	Not Applicable		
.5. Environmental hazard	Environmentally hazardous		
	Special provisions		A145 A167 A802
	Cargo Only Packing Instructions	203	
	Cargo Only Maximum Qty / Pack	150 kg	
4.6. Special precautions for user	Passenger and Cargo Packing In	203	
101 4301	Passenger and Cargo Maximum	75 kg	
	Passenger and Cargo Limited Qu	Y203	
	Passenger and Cargo Limited Ma	30 kg G	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950			
14.2. UN proper shipping name	AEROSOLS			
14.3. Transport hazard class(es)	IMDG Class	azard	2.1 Not Applicable	
14.4. Packing group	Not Applicable	Not Applicable		
14.5 Environmental hazard	Marine Pollutant			
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	EMS Number F-D , S-U Special provisions 63 190 277 327 344 381 959		

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
mineral oil	Not Available
2-methylpentane	Not Available

Product name	Group
hydrocarbon propellant	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
mineral oil	Not Available
2-methylpentane	Not Available
hydrocarbon propellant	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002515	Aerosols (Flammable) Group Standard 2017	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

mineral oil is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International Agency fsor Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Workplace Exposure Standards (WES)

2-methylpentane is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

hydrocarbon propellant is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)	
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)	

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	No (mineral oil)	
Canada - DSL	No (mineral oil)	
Canada - NDSL	No (mineral oil; 2-methylpentane; hydrocarbon propellant)	
China - IECSC	No (mineral oil)	
Europe - EINEC / ELINCS / NLP	No (mineral oil)	
Japan - ENCS	Yes	
Korea - KECI	No (mineral oil)	
New Zealand - NZIoC	No (mineral oil)	
Philippines - PICCS	No (mineral oil)	
USA - TSCA	TSCA Inventory 'Active' substance(s) (2-methylpentane; hydrocarbon propellant); No (mineral oil)	
Taiwan - TCSI	No (mineral oil)	
Mexico - INSQ	No (mineral oil)	
Vietnam - NCI	No (mineral oil)	
Russia - FBEPH	No (mineral oil)	
Yes = All CAS declared ingredients are on the inventory Legend: No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	10/12/2021
Initial Date	09/05/2005

SDS Version Summary

Version	Date of Update	Sections Updated	
6.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification	
7.1	10/12/2021	Classification change due to full database hazard calculation/update.	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.