

# **CRC Mass Air Flow Sensor Cleaner CRC Industries (CRC Industries New Zealand)**

Chemwatch Hazard Alert Code:

Issue Date: **10/03/2023**Print Date: **17/10/2024**S.GHS.NZL.EN

Version No: **9.1**Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Chemwatch: 4837-14

Product name	CRC Mass Air Flow Sensor Cleaner
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Mass air flow sensor cleaner.  The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.  Application is by spray atomisation from a hand held aerosol pack
--------------------------	--

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	0 Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	- No EMAL ID NEEDED for NZ - JACK	

### **Emergency telephone number**

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112
Other emergency telephone number(s)	111 (NZ Emergency Services)	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

#### **SECTION 2 Hazards identification**

### Classification of the substance or mixture

Classification <sup>[1]</sup>	Aerosols, Hazard Category 1, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 2		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.1E (aspiration), 6.4A, 6.8B, 6.9A, 9.1B		

#### Hazard pictogram(s)









Signal word

Danger

### Hazard statement(s)

H222+H229	H229 Extremely flammable aerosol. Pressurized container: may burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H319	Causes serious eye irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H372	H372 Causes damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	

#### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	

#### Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331	Do NOT induce vomiting.	
P308+P313	3 IF exposed or concerned: Get medical advice/ attention.	
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rin		

### Precautionary statement(s) Storage

P405	Store locked up.	
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.		

### Precautionary statement(s) Disposal

**P501** Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### **SECTION 3 Composition / information on ingredients**

### Substances

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name
107-83-5	80-90	2-methylpentane
110-54-3	1-10	n-hexane
64742-48-9.	1-10	naphtha petroleum, heavy, hydrotreated
67-56-1	<1	methanol
124-38-9	2-5	carbon dioxide
Legend:	•	Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No iffication drawn from C&L * EU IOELVs available

### **SECTION 4 First aid measures**

#### Description of first aid measures

### **Eye Contact**

If aerosols come in contact with the eyes:

- Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Transport to hospital or doctor without delay.

	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.		
Skin Contact	If solids or aerosol mists are deposited upon the skin:  Flush skin and hair with running water (and soap if available).  Remove any adhering solids with industrial skin cleansing cream.  DO NOT use solvents.  Seek medical attention in the event of irritation.		
Inhalation	If aerosols, fumes or combustion products are inhaled:  Remove to fresh air.  Lay patient down. Keep warm and rested.  Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.  If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.  Transport to hospital, or doctor.		
Ingestion	<ul> <li>Not considered a normal route of entry.</li> <li>If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> </ul>		

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 Firefighting measures**

#### **Extinguishing media**

SMALL FIRE:

▶ Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

#### Special hazards arising from the substrate or mixture

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

### Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Liquid and vapour are highly flammable.</li> <li>Severe fire hazard when exposed to heat or flame.</li> <li>Vapour forms an explosive mixture with air.</li> <li>Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> <li>Other combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit clouds of acrid smoke</li> <li>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.</li> </ul>

### **SECTION 6 Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Wear protective clothing, impervious gloves and safety glasses.</li> <li>Shut off all possible sources of ignition and increase ventilation.</li> </ul>
Major Spills	<ul> <li>Remove leaking cylinders to a safe place if possible.</li> <li>Release pressure under safe, controlled conditions by opening the valve.</li> <li>DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>

- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 Handling and storage**

#### Precautions for safe handling

Safe handling	<ul> <li>Containers, even those that have been emptied, may contain explosive vapours.</li> <li>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>Store in original containers in approved flammable liquid storage area.</li> <li>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</li> <li>No smoking, naked lights, heat or ignition sources.</li> <li>Keep containers securely sealed.</li> </ul>

### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Aerosol dispenser.</li> <li>Check that containers are clearly labelled.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

### SECTION 8 Exposure controls / personal protection

### **Control parameters**

### Occupational Exposure Limits (OEL)

### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	n-hexane	Hexane (n- Hexane)	20 ppm / 72 mg/m3	Not Available	Not Available	(bio) - Exposure can also be estimated by biological monitoring oto - Ototoxin
New Zealand Workplace Exposure Standards (WES)	n-hexane	Hexane, Other isomers	500 ppm / 1760 mg/m3	3500 mg/m3 / 1000 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	naphtha petroleum, heavy, hydrotreated	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	methanol	Methanol (Methyl alcohol)	200 ppm / 262 mg/m3	328 mg/m3 / 250 ppm	Not Available	(skin) - Skin absorption (bio) - Exposure can also be estimated by biological monitoring
New Zealand Workplace Exposure Standards (WES)	carbon dioxide	Carbon dioxide	5000 ppm / 9000 mg/m3	54000 mg/m3 / 30000 ppm	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
2-methylpentane	Not Available	Not Available
n-hexane	Not Available	Not Available
naphtha petroleum, heavy, hydrotreated	2,500 mg/m3	Not Available
methanol	6,000 ppm	Not Available
carbon dioxide	40,000 ppm	Not Available

#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
2-methylpentane	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

# Appropriate engineering controls

**CARE:** Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Individual protection measures, such as personal protective equipment









#### Eye and face protection

- ▶ No special equipment for minor exposure i.e. when handling small quantities.
- ▶ OTHERWISE: For potentially moderate or heavy exposures:
- Safety glasses with side shields.
- ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

#### Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

#### Hands/feet protection

Personal hygiene is a key element of effective hand care.

- ▶ No special equipment needed when handling small quantities.
- OTHERWISE:
- ▶ For potentially moderate exposures:
- ▶ Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

#### **Body protection**

See Other protection below

## Other protection

- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
- ▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERICK: Handbook of Reactive Chemical Hazards.

No special equipment needed when handling small quantities.

CDI

#### INO

- OTHERWISE:
   Overalls.
- ▶ Skin cleansing cream.
- ▶ Eyewash unit.

#### Recommended material(s)

#### **GLOVE SELECTION INDEX**

Motorial

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

CRC Mass Air Flow Sensor Cleaner

Material	CPI
PE/EVAL/PE	Α
SARANEX-23 2-PLY	Α
TEFLON	В
BUTYL	С
BUTYL/NEOPRENE	С
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PVA	С
PVC	С
PVDC/PE/PVDC	С

#### Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P3	-	AX-PAPR-AUS / Class 1 P3
up to 50 x ES	-	AX-AUS / Class 1 P3	-
up to 100 x ES	-	AX-2 P3	AX-PAPR-2 P3 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SARANEX-23	С
VITON	С
VITON/CHLOROBUTYL	С
VITON/NEOPRENE	С

<sup>\*</sup> CPI - Chemwatch Performance Index

A: Best Selection

- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove,

- a final selection must be based on detailed observation. -
- \* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance	Clear flammable liquid aerosol with an alcoholic odour; insoluble in water.		
7 <b>.</b>	Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant.		

Physical state	Liquid	Relative density (Water = 1)	0.6699
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	<-17.78	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	60.56	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	<-17.78 (TCC)	Taste	Not Available
Evaporation rate	>1 BuAC = 1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.7	Volatile Component (%vol)	95 (VOC)
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Elevated temperatures.</li> <li>Presence of open flame.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

Information on toxicologic	al effects
Inhaled	Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.  There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.  Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.  If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.  Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.  WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.
Ingestion	Not normally a hazard due to physical form of product.  Considered an unlikely route of entry in commercial/industrial environments  Accidental ingestion of the material may be damaging to the health of the individual.  Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)  Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.
Skin Contact	Spray mist may produce discomfort The material may accentuate any pre-existing dermatitis condition Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged.  Aromatic species can cause irritation and excessive tear secretion.  There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.
Chronic	Main route of exposure to the gas in the workplace is by inhalation.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Harmful: danger of serious damage to health by prolonged exposure through inhalation.

CRC Mass Air Flow Sensor	TOXICITY	IRRITATION
Cleaner	Not Available	Not Available
	TOXICITY	IRRITATION
2-methylpentane	Oral (Rat) LD50: ~15.84 mg/kg <sup>[1]</sup>	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 10mg - Mild
n-hexane	Inhalation (Rat) LC50: 48000 ppm4h <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rat) LD50: 28710 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
naphtha petroleum, heavy,	Dermal (rabbit) LD50: >1900 mg/kg <sup>[1]</sup>	Not Available
hydrotreated	Inhalation (Rat) LC50: >4.42 mg/L4h <sup>[1]</sup>	
	Oral (Rat) LD50: >4500 mg/kg <sup>[1]</sup>	
methanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 15800 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 0.1mL

Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.

which can produce severe defects.

Inhalation (Rat) LC50: 64000 ppm4h<sup>[2]</sup>

Oral (Rat) LD50: 5628 mg/kg<sup>[2]</sup>

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance

Eye (Rodent - rabbit): 0.1mL - Severe

Eye (Rodent - rabbit): 100mg/24H - Moderate Eye (Rodent - rabbit): 40mg - Moderate

		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (Rodent - rabbit): 20mg/24H - Moderate
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
carbon dioxide	Not Available	Not Available
Legend:	1 Value obtained from Europe ECHA Pogiete	ered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.

2-METHYLPENTANE	No significant acute toxicological data identified	in literature search.	
N-HEXANE	The material may be irritating to the eye, with pr irritants may produce conjunctivitis.	rolonged contact causing inflamm	ation. Repeated or prolonged exposure to
NAPHTHA PETROLEUM, HEAVY, HYDROTREATED	Animal studies indicate that normal, branched a absorption of n-paraffins is inversely proportional carbon chain lengths likely to be present in mine paraffins.  The major classes of hydrocarbons are well absolute hydrophobic hydrocarbons are ingested in assolute lipoprotein particles in the gut lymph, but most help the petroleum contains aromatic (benzene, toluene result in many detrimental health effects, including Animal testing shows breathing in petroleum carelevant in humans. Similarly, exposure to gason humans is questionable.  Most studies involving gasoline have shown that human subjects (such as in petrol service station Animal studies show concentrations of toluene in developmental toxicity to the nervous system of Prolonged contact with petroleum may result in by other materials.	al to the carbon chain length, with eral oil, n-paraffins may be absorbed into the gastrointestinal traciation with fats in the diet. Some hydrocarbons partly separate from, ethyl benzene, napthalene) and ing, cancer, tumour formation, here uses tumours of the liver and kidraline over a lifetime can cause kidrat gasoline does not cause genetic at tall the foetus. Other studies show n	little absorption above C30. With respect to the ped to a greater extent than iso- or cyclo- act in various species. In many cases, the hydrocarbons may appear unchanged as in the fats and undergo metabolism in the gut cell. aliphatic hydrocarbons (n-hexane), which can aring loss, and nervous system toxicity. They; these are however not considered to be ney cancer in animals, but the relevance in a mutation, including all recent studies in living all effects such as lower birth weight and to adverse effects on the foetus.
METHANOL	The material may cause skin irritation after prole the production of vesicles, scaling and thickenin		may produce on contact skin redness, swelling,
Acute Toxicity	x	Carcinogenicity	x
Skin Irritation/Corrosion	×	Reproductivity	~
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	<b>~</b>

**Legend:** X − Data either not available or does not fill the criteria for classification 
✓ − Data available to make classification

### **SECTION 12 Ecological information**

#### Toxicity

oxicity					
	Endpoint	Test Duration (hr)	Species	Value	Source
CRC Mass Air Flow Sensor Cleaner	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
2-methylpentane	EC50(ECx)	96h	Algae or other aquatic plants	4.321mg/l	2
	EC50	96h	Algae or other aquatic plants	4.321mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
n-hexane	EC50(ECx)	4h	Algae or other aquatic plants	0.12mg/L	4
	LC50	96h	Fish	113mg/L	4
	Endpoint	Test Duration (hr)	Species	Value	Source
naphtha petroleum, heavy,	EC50	48h	Crustacea	>0.002mg/l	2
hydrotreated	EC50(ECx)	48h	Crustacea	>0.002mg/l	2
	EC50	96h	Algae or other aquatic plants	64mg/l	2

	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	>10000mg/l	2
methanol	NOEC(ECx)	720h	Fish	0.007mg/L	4
menanor	LC50	96h	Fish	290mg/l	2
	EC50	96h	Algae or other aquatic plants	14.11- 20.623mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
carbon dioxide	LC50	96h	Fish	35mg/l	1
Legend:	4. US EPA, Eco	1. IUCLID Toxicity Data 2. Europe ECHA Rotox database - Aquatic Toxicity Data 5. ECon Data 7. METI (Japan) - Bioconcentration	ETOC Aquatic Hazard Assessment Data	•	atic Toxicity

For Hydrocarbons: log Kow 1. BCF~10.

For Aromatics: log Kow 2-3.

BCF 20-200.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-methylpentane	LOW	LOW
n-hexane	LOW	LOW
methanol	LOW	LOW
carbon dioxide	LOW	LOW

### **Bioaccumulative potential**

Ingredient	Bioaccumulation
2-methylpentane	LOW (LogKOW = 3.2145)
n-hexane	MEDIUM (LogKOW = 3.9)
methanol	LOW (BCF = 10)
carbon dioxide	LOW (LogKOW = 0.83)

### Mobility in soil

Ingredient	Mobility
2-methylpentane	LOW (Log KOC = 124.9)
n-hexane	LOW (Log KOC = 149)
methanol	HIGH (Log KOC = 1)
carbon dioxide	HIGH (Log KOC = 1.498)

#### **SECTION 13 Disposal considerations**

### Waste treatment methods

Product / Packaging disposal

- ▶ Consult State Land Waste Management Authority for disposal.
- ▶ Discharge contents of damaged aerosol cans at an approved site.
- ▶ Allow small quantities to evaporate.
- ▶ DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

### **SECTION 14 Transport information**

### **Labels Required**



### Marine Pollutant



HAZCHEM

Not Applicable

### Land transport (UN)

14.1. UN number or ID number	1950	
14.2. UN proper shipping name	AEROSOLS	
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.1 Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Environmentally haza	rdous
14.6. Special precautions for user	Special provisions Limited quantity	63; 190; 277; 327; 344; 381 1000ml

### Air transport (ICAO-IATA / DGR)

14.1. UN number	1950		
14.2. UN proper shipping name	Aerosols, flammable		
	ICAO/IATA Class	2.1	
4.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
ciass(es)	ERG Code	10L	
4.4. Packing group	Not Applicable		
4.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions	Special provisions	
	Cargo Only Packing Instructions		203
	Cargo Only Maximum Qty / Pack		150 kg
	Passenger and Cargo Packing In	Passenger and Cargo Packing Instructions	
	Passenger and Cargo Maximum	Passenger and Cargo Maximum Qty / Pack	
	Passenger and Cargo Limited Qu	Passenger and Cargo Limited Quantity Packing Instructions	
	Passenger and Cargo Limited Maximum Qty / Pack		30 kg G

### Sea transport (IMDG-Code / GGVSee)

• •	,		
14.1. UN number	1950		
14.2. UN proper shipping name	AEROSOLS		
14.3. Transport hazard class(es)	IMDG Class	2.1	
	IMDG Subsidiary Hazard	Not Applicable	
14.4. Packing group	Not Applicable		
14.5 Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	EMS Number F-D , S-U		

Special provisions	63 190 277 327 344 381 959	
Limited Quantities	1000 ml	

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2-methylpentane	Not Available
n-hexane	Not Available
naphtha petroleum, heavy, hydrotreated	Not Available
methanol	Not Available
carbon dioxide	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
2-methylpentane	Not Available
n-hexane	Not Available
naphtha petroleum, heavy, hydrotreated	Not Available
methanol	Not Available
carbon dioxide	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002515	Aerosols (Flammable) Group Standard 2017	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### 2-methylpentane is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

#### n-hexane is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### naphtha petroleum, heavy, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

New Zealand Workplace Exposure Standards (WES)

### methanol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

 $New\ Zealand\ Hazardous\ Substances\ and\ New\ Organisms\ (HSNO)\ Act\ -\ Classification\ of\ Chemicals$ 

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### carbon dioxide is found on the following regulatory lists

FEI Equine Prohibited Substances List - Controlled Medication

FEI Equine Prohibited Substances List (EPSL)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### **Additional Regulatory Information**

Not Applicable

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

#### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

#### **Tracking Requirements**

Not Applicable

### **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (2-methylpentane; n-hexane; naphtha petroleum, heavy, hydrotreated; methanol; carbon dioxide)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	Yes		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

#### **SECTION 16 Other information**

#### **SDS Version Summary**

Version	Date of Update	Sections Updated	
8.1	10/12/2021	Classification change due to full database hazard calculation/update.	
9.1	10/03/2023	Classification change due to full database hazard calculation/update.	

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.