

CRC RTV Siliicone Neutral Cure CRC Industries (CRC Industries New Zealand)

CRC Industries (CRC Industries New Zealand)
Chemwatch: 6015-12

Version No: **4.1**Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 2

Issue Date: **01/11/2019**Print Date: **11/08/2022**S GHS NZL EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	CRC RTV Siliicone Neutral Cure	
Chemical Name	Not Applicable	
Synonyms	silicone sealant	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant	identified	uses

A multipurpose silicone sealant for glazing and sealing applications.

Applied using a hand trowel or spreader

Cured material solid has high heat resistance, is practically non combustible, but is decomposed by near red heat

Details of the supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	10 Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	+64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	customerservices@crc.co.nz	

Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112
Other emergency telephone numbers	111 (NZ Emergency Services)	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Serious Eye Damage/Eye Irritation Category 1, Hazardous to Terrestrial Invertebrates, Skin Corrosion/Irritation Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 8.3A, 9.4B

Label elements

Hazard pictogram(s)







Signal word	Danger	

Hazard statement(s)

H318	Causes serious eye damage.
H442	Hazardous to terrestrial invertebrates.
H315	Causes skin irritation.

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
70131-67-8	>=60	dimethylsiloxane, hydroxy-terminated
4253-34-3	<=10	<u>methyltriacetoxysilane</u>
Not Available	10-30	fillers and plasticisers, non-hazardous
Not Available		Not Available
Not Available		NOTE: During curing or on exposure to moist air
Not Available		product generates acetic acid
64-19-7		acetic acid glacial
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	Wipe off excess with absorbent tissue or towel. Wash affected areas with warm water and soap. Seek medical attention if swelling/redness/blistering or irritation occurs.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.

For advice, contact a Poisons Information Centre or a doctor at once.

- Urgent hospital treatment is likely to be needed.
- ▶ If swallowed do **NOT** induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Ingestion

Extinguishing media

- Water spray or fog.
- Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Avoid reaction with strong oxidisers

Advice for firefighters

Advice for intelligitiers	
Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. Wear self-contained breathing apparatus and full body protective clothing including boots. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	Uncured material paste is combustible, i.e. will burn if ignited. Not considered a significant fire risk. Heat may cause expansion leading to rupture of containers and contents spill High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers. These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite. An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wipe up and absorb small quantities with vermiculite or other absorbent material. Place in suitable containers for disposal.
Major Spills	Clear area of personnel. • Wear full body protective clothing with breathing apparatus. • Prevent, by any means available, spillage from entering drains or water courses. Shut off all possible sources of ignition and increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Scrape up the cured (hardened) substance. Collect and seal in labelled drums for disposal

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Use good occupational work practice.

Safe handling Avoid breathing vapours and contact with skin and eyes

► Avoid reaction with oxidising agents

Avoid sources of heat.
Avoid physical damage to containers.

Wear personal protective equipment when handling
When handling, DO NOT eat, drink or smoke.
Use in a well-ventilated area
until atmosphere has been checked.
Always wash hands with soap and water after handling. Work clothes should be laundered separately.

Store in original containers.

Keep containers securely sealed.

Store in a cool, dry, well-ventilated area.

Store away from incompatible materials and foodstuff containers.

Avoid storage with oxidisers

Conditions for safe storage, including any incompatibilities

Suitable container	Aluminium tubes. Plastic cartridge Check that containers are clearly labelled
Storage incompatibility	Avoid storage with oxidisers

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	acetic acid glacial	Acetic acid	10 ppm / 25 mg/m3	37 mg/m3 / 15 ppm	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
dimethylsiloxane, hydroxy- terminated	190 mg/m3	2,100 mg/m3	13,000 mg/m3
methyltriacetoxysilane	5 mg/m3	35 mg/m3	250 mg/m3
acetic acid glacial	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
dimethylsiloxane, hydroxy- terminated	Not Available	Not Available
methyltriacetoxysilane	Not Available	Not Available
acetic acid glacial	50 ppm	Not Available

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions. If inhalation risk of overexposure exists, wear SAA approved acid-vapour respirator.
Personal protection	
Eye and face protection	► Safety glasses. ► Eyewash unit.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves. e.g. PVC gloves with barrier cream Wear safety footwear.
Body protection	See Other protection below
Other protection	Overalls

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

CRC RTV Siliicone Neutral Cure

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Material	СРІ
BUTYL	A
NEOPRENE	A
NITRILE+PVC	A
PE	A
PE/EVAL/PE	A
PVC	A
SARANEX-23	A
TEFLON	A
BUTYL/NEOPRENE	В
NATURAL RUBBER	В
NATURAL+NEOPRENE	В
NITRILE	В
NAT+NEOPR+NITRILE	С

* CPI - Chemwatch Performance Inde	
	,

A: Best Selection

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AB-AUS P2	-	AB-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AB-AUS / Class 1 P2	-
up to 100 x ES	-	AB-2 P2	AB-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Smooth translucent colourless paste with acetic acid-like odour; does not mix with water. Prior to setting, soluble in organic solvents such as mineral turpentine, toluene. Once set, insoluble in all known solvents.

Material cures / solidifies by reacting with atmospheric moisture and this process generates irritating acetic acid vapour

Physical state	Non Slump Paste	Relative density (Water = 1)	1.035-1.045
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	< 8
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable
Vapour density (Air = 1)	> 1	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.

B: Satisfactory; may degrade after 4 hours continuous immersion

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled The vapour from the curing material is discomforting if inhaled Considered an unlikely route of entry in commercial/industrial environments The material is regarded as non-toxic if swallowed but may be harmful if swallowed but may be harmful if swallowed in large quantity if small amounts may be highly irritating to sensitive mouth parts and in extreme cases produce small blisters but no toxic effects are known. Smoothing the sealant with saliva wet finger may introduce sealant into the mouth. Safer alternates should replace this poor work practice. Skin Contact Skin Contact Skin Contact In material is moderately discomforting to the skin and may cause reddening and swelling and even blisters or burns if exposure is prolonged however substance may be an allergen. Irritating to eyes. The material is moderately discomforting to the eyes and may cause reddening and swelling and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated Principal routes of exposure are usually by skin contacted yet contact with the material and inhalation of vapour from the curing material	illiormation on toxicologi	cal effects
Ingestion Ingest	Inhaled	discomforting
to the skin and may cause reddening and swelling and even blisters or burns if exposure is prolonged however Substance may be an allergen. Irritating to eyes. The material is moderately discomforting to the eyes and may cause reddening and swelling and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated Principal routes of exposure are usually by skin contact/eye contact with the material and	Ingestion	The material is regarded as non-toxic if swallowed but may be harmful if swallowed in large quantity Small amounts may be highly irritating to sensitive mouth parts and in extreme cases produce small blisters but no toxic effects are known. Smoothing the sealant with saliva wet finger may introduce sealant into the mouth. Safer alternates should replace this poor work
The material is moderately discomforting to the eyes and may cause reddening and swelling and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated Principal routes of exposure are usually by skin contact/eye contact with the material and	Skin Contact	to the skin and may cause reddening and swelling and even blisters or burns if exposure is prolonged however
skin contact/eye contact Chronic with the material and	Еуе	The material is moderately discomforting to the eyes and may cause reddening and swelling and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if
	Chronic	skin contact/eye contact with the material and

RC RTV Siliicone Neutral	TOXICITY	IRRITATION
Cure	Not Available	Not Available
	TOXICITY	IRRITATION
imethylsiloxane, hydroxy- terminated	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Not Available
terminated	Oral (Rat) LD50; >5000 mg/kg ^[2]	
	TOXICITY	IRRITATION
methyltriacetoxysilane	Oral (Rat) LD50; 1550 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]
		Skin: adverse effect observed (corrosive) ^[1]
CRC RTV Siliicone Neutral Cure		
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1060 mg/kg ^[2]	Eye (rabbit): 0.05mg (open)-SEVERE
acetic acid glacial	Inhalation(Mouse) LC50; 1.405 mg/L4h ^[2]	Skin (human):50mg/24hr - mild
	Oral (Rat) LD50; 3310 mg/kg ^[2]	Skin (rabbit):525mg (open)-SEVERE
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

DIMETHYLSILOXANE, S HYDROXY-TERMINATED t	* [Mobay Chemical Corp] **[GE] Siloxanes may impair liver and hormonal function the skin and eyes. They may potentially cause of infertility.		
METHYLTRIACETOXYSILANE b d	The material may produce moderate eye irritation produce conjunctivitis. The material may produce respiratory tract irritation after produce respiratory tract irritation. The material may cause skin irritation after production of vesicles, scaling and Clinical signs of acute methyltriacetoxysilane pobreathing, rales, red stains around the snout an lethargy, irregular gait, hunched posture, red uri Autopsy showed multiple abnormalities of the stand corrosive to the eyes of animals; as it is bro Tests on laboratory cells have not shown methy	tion, and result in damage to the onged or repeated exposure and thickening of the skin. visoning in animals include decred extremities, salivation, excessination, black/brown anogenital stromach. Methyltriacetoxysilane is ken down by water to acetic acid	lung including reduced lung function. may produce on contact skin redness, ased body weight and food intake, labored we tear (sometimes coloured) production, taining, paleness, and low body temperature. s severely irritating and corrosive to the skin, d, it is likely to irritate the airway.
ACETIC ACID GLACIAL	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from to respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from dire exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged expost irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin respectively.		protect the cells of the airway from direct hydrochloric acid secreted there). Inmation. Repeated or prolonged exposure to the airway produce on contact skin redness,
METHYLTRIACETOXYSILANE & ACETIC ACID GLACIAL ii F	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. Prolonged or repeated exposure to acetic acid may produce irritation and/ or corrosion at the site of contact as well as systemic toxicity. Prolonged inhalation exposure results in muscle imbalance, increase in blood cholinesterase activity, decrease in albumin and decreased growth but no reproductive or foetal toxicity, according to animal testing.		
Acute Toxicity X		Carcinogenicity	x

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

2

29.23mg/l

✓ – Data available to make classification

Algae or other aquatic plants

SECTION 12 Ecological information

EC50

72h

oxicity					
CRC RTV Siliicone Neutral Cure	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
P	Endpoint	Test Duration (hr)	Species	Value	Source
dimethylsiloxane, hydroxy- terminated	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	>=3.6mg/l	2
methyltriacetoxysilane	EC50	72h	Algae or other aquatic plants	>3.6mg/l	2
	EC50	48h	Crustacea	65mg/l	2
	LC50	96h	Fish	>=79<=88mg/l	2
CRC RTV Siliicone Neutral Cure					
	Endpoint	Test Duration (hr)	Species	Value	Source
acetic acid glacial	EC50(ECx)	24h	Algae or other aquatic plants	0.08mg/l	2
and an					

	EC50	48h	Crustacea	18.9mg/l	2
	LC50	96h	Fish	31.3-67.6mg/l	2
Legend:	4. US EPA, Eco	, ,	Registered Substances - Ecotoxicological I CETOC Aquatic Hazard Assessment Data on Data 8. Vendor Data	•	tic Toxicity

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methyltriacetoxysilane	HIGH	HIGH
acetic acid glacial	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
methyltriacetoxysilane	LOW (LogKOW = 0.2467)
acetic acid glacial	LOW (LogKOW = -0.17)

Mobility in soil

Ingredient	Mobility
methyltriacetoxysilane	LOW (KOC = 35.19)
acetic acid glacial	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging	Bury or incinerate residue at an approved site.
disposal	Bury empty containers at an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

•	
Product name	Group
dimethylsiloxane, hydroxy- terminated	Not Available
methyltriacetoxysilane	Not Available
acetic acid glacial	Not Available

Transport in bulk in accordance with the ICG Code

roduct name	Ship Type
Todact Harric	Cinp Type

Product name	Ship Type
dimethylsiloxane, hydroxy- terminated	Not Available
methyltriacetoxysilane	Not Available
acetic acid glacial	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

dimethylsiloxane, hydroxy-terminated is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

methyltriacetoxysilane is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals - Classification Data New Zealand Inventory of Chemicals (NZIoC)

Not Applicable

acetic acid glacial is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC) New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (dimethylsiloxane, hydroxy-terminated; methyltriacetoxysilane; acetic acid glacial)	
China - IECSC	Yes	

National Inventory	Status	
Europe - EINEC / ELINCS / NLP	No (dimethylsiloxane, hydroxy-terminated)	
Japan - ENCS	No (dimethylsiloxane, hydroxy-terminated)	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	01/11/2019
Initial Date	01/11/2009

SDS Version Summary

Version	Date of Update	Sections Updated
3.1	27/06/2017	Classification, Ingredients
4.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard
OSF: Odour Safety Factor

NOAEL : No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value

LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.