

CRC 8370, 8380 Gasket 260 Red Gasket 200 Trans (NZ)

CRC Industries (CRC Industries New Zealand)

Chemwatch: 4574-10 Version No: 6.1.1.1

Chemwatch Hazard Alert Code: 2

Issue Date: 01/11/2019 Print Date: 03/04/2020 S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	CRC 8370, 8380 Gasket 260 Red Gasket 200 Trans (NZ)	
Synonyms	silicone sealant	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Formed in place gaskets on metal surfaces.

Details of the supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	
Address	10 Highbrook Drive East Tamaki Auckland New Zealand	
Telephone	+64 9 272 2700	
Fax	+64 9 274 9696	
Website	www.crc.co.nz	
Email	customerservices@crc.co.nz	

Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)	
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)	
Other emergency telephone numbers	111 (NZ Emergency Services)	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Acute Invertebrate Hazard Category 2		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 8.3A, 9.4B		

Label elements

Hazard pictogram(s)			*
---------------------	--	--	---

DANGER

SIGNAL WORD Hazard statement(s)

H315	Causes skin irritation.
H318	Causes serious eye damage.
H442	Toxic to terrestrial invertebrates

Precautionary statement(s) Prevention

- -	
P273	Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P321	Specific treatment (see advice on this label).	
P391	Collect spillage.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
70131-67-8	30-60	dimethylsiloxane. hydroxy-terminated
4253-34-3	1-9.9	methyltriacetoxysilane
Not Available	10-30	fillers and plasticisers, non-hazardous
Not Available		NOTE: During curing or on exposure to moist air
Not Available		product generates acetic acid
64-19-7		acetic acid glacial

SECTION 4 FIRST AID MEASURES

Description of first aid measures

-		
Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 	
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. 	
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. 	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. 	

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition result		
Advice for firefighters		
	 Alert Fire Brigade and tell them location and nature of hazard. 	
Fire Fighting	 Wear breathing apparatus plus protective gloves in the event of a fire. 	

Prevent, by any means available, spillage from entering drains or water courses.

	Use fire fighting procedures suitable for surrounding area.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Clean up all spills immediately. Avoid breathing vapours/ aerosols or dusts and avoid contact with skin and eyes. Place in a suitable, labelled container for waste disposal.
Major Spills	 Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer.
Storage incompatibility	 Avoid strong bases. Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	acetic acid glacial	Acetic acid	10 ppm / 25 mg/m3	37 mg/m3 / 15 ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
dimethylsiloxane, hydroxy- terminated	Dimethyl(polysiloxane); (Polydimethylsiloxane, silanol terminated; Dimethylsiloxane, poly, hydroxy end-blocked)	190 mg/m3	2,100 mg/m3	13,000 mg/m3
methyltriacetoxysilane	Methyltriacetoxysilane	5 mg/m3	35 mg/m3	250 mg/m3

acetic acid glacial	Acetic acid		Not Available	Not Available	Not Available
Ingredient	Original IDLH	Revised IDLH			
dimethylsiloxane, hydroxy- terminated	Not Available	Not Available			
methyltriacetoxysilane	Not Available	Not Available			
acetic acid glacial	50 ppm	Not Available			

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream.

Recommended material(s)

GLOVE SELECTION INDEX

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AB-AUS P2	-	AB-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AB-AUS / Class 1 P2	-
up to 100 x ES	-	AB-2 P2	AB-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC) Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the

computer-generated selection: CRC 8370, 8380 Gasket 260 Red Gasket 200 Trans (NZ)

Material	CPI
BUTYL	А
NEOPRENE	А
NITRILE+PVC	A
PE	A
PE/EVAL/PE	A
PVC	A
SARANEX-23	A
TEFLON	A
BUTYL/NEOPRENE	В
NATURAL RUBBER	В
NATURAL+NEOPRENE	В
NITRILE	В
NAT+NEOPR+NITRILE	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear/ red paste; not miscible with water.		
Physical state	Non Slump Paste	Relative density (Water = 1)	1.035-1.045
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	<8
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.	
Ingestion	Smoothing the sealant with saliva wet finger may introduce sealant into the mouth. Safer alternates should replace this poor work practice.	
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin	
Eye	This material can cause eye irritation and damage in some persons.	
Chronic	Chronic Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directive using animal models); nevertheless exposure by all routes should be minimised as a matter of course.	

CRC 8370, 8380 Gasket	TOXICITY	IRRITATION
260 Red Gasket 200 Trans (NZ)	Not Available	Not Available
	ΤΟΧΙΟΙΤΥ	IRRITATION
dimethylsiloxane, hydroxy-	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Not Available
terminated	Inhalation (rat) LC50: >15.3125 mg/l/7H ^[2]	
	Oral (rat) LD50: >5000 mg/kg ^[2]	
	ТОХІСІТҮ	IRRITATION
methyltriacetoxysilane	Oral (rat) LD50: 1550 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]
		Skin: adverse effect observed (corrosive) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1060 mg/kg ^[2]	Eye (rabbit): 0.05mg (open)-SEVERE
acetic acid glacial	Inhalation (rat) LC50: 11 mg/l/4H ^[2]	Skin (human):50mg/24hr - mild
	Oral (rat) LD50: 3310 mg/kg ^[2]	Skin (rabbit):525mg (open)-SEVERE
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 	

DIMETHYLSILOXANE, HYDROXY-TERMINATED	* [Mobay Chemical Corp] **[GE] Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility.
METHYLTRIACETOXYSILANE	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Clinical signs of acute methyltriacetoxysilane poisoning in animals include decreased body weight and food intake, labored breathing, rales, red stains around the snout and extremities, salivation, excessive tear (sometimes coloured) production, lethargy, irregular gait, hunched posture, red urination, black/brown anogenital staining, paleness, and low body temperature. Autopsy showed multiple abnormalities of the stomach. Methyltriacetoxysilane is severely irritating and corrosive to the skin, and corrosive to the eyes of animals; as it is broken down by water to acetic acid, it is likely to irritate the airway. Tests on laboratory cells have not shown methyltriacetoxysilane to cause mutations or chromosomal aberrations.
ACETIC ACID GLACIAL	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

CRC 8370, 8380 Gasket 260 Red Gasket 200 Trans (NZ)

METHYLTRIACETOXYSILANE & ACETIC ACID GLACIAL

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

Prolonged or repeated exposure to acetic acid may produce irritation and/ or corrosion at the site of contact as well as systemic toxicity. Prolonged inhalation exposure results in muscle imbalance, increase in blood cholinesterase activity, decrease in albumin and decreased growth but no reproductive or foetal toxicity, according to animal testing.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

- Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

CRC 8370, 8380 Gasket 260 Red Gasket 200 Trans (NZ)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
dimethylsiloxane, hydroxy- terminated	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	8-950mg/L	2
methyltriacetoxysilane	EC50	48	Crustacea	65mg/L	2
	EC50	72	Algae or other aquatic plants	>1-386mg/L	2
	NOEC	72	Algae or other aquatic plants	>=3.6mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
acetic acid glacial	EC50	48	Crustacea	>1-mg/L	2
	EC50	72	Algae or other aquatic plants	Algae or other aquatic plants >1-mg/L	
	NOEC	72	Algae or other aquatic plants	1-mg/L	2
Legend:	3. EPIWIN Su	ite V3.12 (QSAR) - Aquatic Toxicit	e ECHA Registered Substances - Ecotoxicol y Data (Estimated) 4. US EPA, Ecotox datab IITE (Japan) - Bioconcentration Data 7. MET	ase - Aquatic Toxicity D	ata 5.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methyltriacetoxysilane	HIGH	HIGH
acetic acid glacial	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
methyltriacetoxysilane	LOW (LogKOW = 0.2467)	
acetic acid glacial	LOW (LogKOW = -0.17)	

Mobility in soil

Ingredient

methyltriacetoxysilane	LOW (KOC = 35.19)	
acetic acid glacial	HIGH (KOC = 1)	

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	Recycle wherever possible or consult manufacturer for recycling options.	
Product / Packaging	Consult State Land Waste Management Authority for disposal.	
disposal	 Bury residue in an authorised landfill. 	
	Recycle containers if possible, or dispose of in an authorised landfill.	

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard		
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017		
DIMETHYLSILOXANE, HYDROXY-TERMINATED IS FOUND ON THE FOLLOWING REGULATORY LISTS			
New Zealand Approved Hazardous Substances with controls New Zealand Hazardous Substances and New Organisms (HSNO) Act		New Zealand Hazardous Substances and New Organisms (HSNO) Act -	
New Zealand Hazardous Substances and New Organisms (HSNO) Act -		Classification of Chemicals - Classification Data	
Classification of Chemicals		New Zealand Inventory of Chemicals (NZIoC)	
METHYLTRIACETOXYSILANE IS FOUND ON THE FOLLOWING REGULATORY LISTS			
New Zealand Approved Hazardous Substances with controls		New Zealand Hazardous Substances and New Organisms (HSNO) Act -	

New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals - Classification Data New Zealand Inventory of Chemicals (NZIoC)

ACETIC ACID GLACIAL IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act - New Zealand Inventory of Chemicals (NZIoC) New Zealand Workplace Exposure Standards (WES)

Hazardous Substance Location

Classification of Chemicals - Classification Data

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers	
Not Applicable	Not Applicable	Not Applicable	

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities	
Not Applicable	Not Applicable	

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status		
Australia - AICS	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (dimethylsiloxane, hydroxy-terminated; methyltriacetoxysilane; acetic acid glacial)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	No (dimethylsiloxane, hydroxy-terminated)		
Japan - ENCS	No (dimethylsiloxane, hydroxy-terminated)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - ARIPS	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 OTHER INFORMATION

Revision Date	01/11/2019
Initial Date	01/11/2009

SDS Version Summary

Version	lssue Date	Sections Updated
4.1.1.1	07/05/2011	Acute Health (skin), Appearance, Classification, Physical Properties, Toxicity and Irritation (Genotox), Toxicity and Irritation (Irritation), Toxicity and Irritation (Toxicity Figure)
6.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.