

# **CRC 9306 Leather Cleaner Aerosol**

# **CRC Industries (CRC Industries New Zealand)**

Chemwatch: 6636-47

Version No: 5.1.1.1 Safety Data Sheet according to HSNO Regulations Chemwatch Hazard Alert Code: 1

Issue Date: 07/03/2020 Print Date: 03/04/2020 S.GHS.NZL.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

# **Product Identifier**

Product name	CRC 9306 Leather Cleaner Aerosol
Synonyms	Not Available
Proper shipping name	AEROSOLS
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Aerosol dispensed foam for the cleaning and conditioning of leather upholstery and furniture.
	The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating
	atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
	Application is by spray atomisation from a hand held aerosol pack

### Details of the supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)	CRC Industries (CRC Industries New Zealand)
Address	PO Box 58 121 Greenmount Auckland New Zealand	10 Highbrook Drive East Tamaki Auckland New Zealand
Telephone	Not Available	+64 9 272 2700
Fax	Not Available	+64 9 274 9696
Website	www.crc.co.nz	www.crc.co.nz
Email	Not Available	customerservices@crc.co.nz

### **Emergency telephone number**

Association / Organisation	CRC Industries (CRC Industries New Zealand)	
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)	
Other emergency telephone numbers	111 (NZ Emergency Services)	

### **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Classification <sup>[1]</sup>	Skin Sensitizer Category 1, Lactation Effects, Specific target organ toxicity - single exposure Category 2, Specific target organ toxicity - repeated exposure Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	6.5B (contact), 6.8C, 6.9B	

#### Label elements



SIGNAL WORD

D WARNING

### Hazard statement(s)

H317

May cause an allergic skin reaction.

H362	May cause harm to breast-fed children.	
H371	May cause damage to organs.	
H373	May cause damage to organs through prolonged or repeated exposure.	

### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P263	Avoid contact during pregnancy and while nursing.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P308+P311	P311 IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.	
P314	Get medical advice/attention if you feel unwell.	

# Precautionary statement(s) Storage

P405	Store locked up.

### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
9016-45-9	0.5-1	nonylphenol, ethoxylated
Not Available	0.2-0.6	fragrance
128-37-0	0.2	2,6-di-tert-butyl-4-methylphenol
7732-18-5	80-90	water
68476-85-7.	5-10	hydrocarbon propellant

# SECTION 4 FIRST AID MEASURES

### Description of first aid measures

Eye Contact	<ul> <li>If aerosols come in contact with the eyes:</li> <li>Immediately hold the eyelids apart and flush the eye with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>		
Skin Contact	<ul> <li>If solids or aerosol mists are deposited upon the skin:</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Remove any adhering solids with industrial skin cleansing cream.</li> <li>DO NOT use solvents.</li> <li>Seek medical attention in the event of irritation.</li> </ul>		
Inhalation	<ul> <li>If aerosols, fumes or combustion products are inhaled:</li> <li>Remove to fresh air.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>		
Ingestion	Not considered a normal route of entry.		

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### Extinguishing media

#### SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

foam.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>		
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered to be a significant fire risk.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>Aerosol cans may explode on exposure to naked flames.</li> <li>Other decomposition products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material.</li> </ul>		

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Wear protective clothing, impervious gloves and safety glasses.</li> <li>Shut off all possible sources of ignition and increase ventilation.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	<ul> <li>Remove leaking cylinders to a safe place if possible.</li> <li>Release pressure under safe, controlled conditions by opening the valve.</li> <li>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

#### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Aerosol dispenser.</li> <li>Check that containers are clearly labelled.</li> </ul>
Storage incompatibility	<ul> <li>CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.</li> <li>Avoid reaction with oxidising agents</li> </ul>

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Not Available

2,000 ppm

# **Control parameters**

# OCCUPATIONAL EXPOSURE LIMITS (OEL)

### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	2,6-di-tert-butyl- 4-methylphenol	2,6-Di-tert-butyl-p-cresol (Butylated hydroxytoluene)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	hydrocarbon propellant	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

### EMERGENCY LIMITS

Ingredient	Material name		TEEL-1	TEEL-2	TEEL-3
nonylphenol, ethoxylated	Glycols, polyethylene, mono(p-nonylphenyl) ether		4.5 mg/m3	49 mg/m3	300 mg/m3
nonylphenol, ethoxylated	Ethoxylated nonylphenol; (Nonyl phenyl polyethylene glycol ether)		43 mg/m3	470 mg/m3	5,400 mg/m3
hydrocarbon propellant	Liquified petroleum gas; (L.P.G.)		65,000 ppm	2.30E+05 ppm	4.00E+05 ppm
Ingredient	Original IDLH	Revise	d IDLH		
nonylphenol, ethoxylated Not Available		Not Av	ailable		
2,6-di-tert-butyl- 4-methylphenol	Not Available	Not Available			

Not Available

Not Available

### OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
nonylphenol, ethoxylated	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

# **Exposure controls**

hydrocarbon propellant

water

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.	
Personal protection		
Eye and face protection	<ul> <li>No special equipment for minor exposure i.e. when handling small quantities.</li> <li>OTHERWISE: For potentially moderate or heavy exposures:</li> <li>Safety glasses with side shields.</li> <li>NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.</li> </ul>	
Skin protection	See Hand protection below	
Hands/feet protection	<ul> <li>No special equipment needed when handling small quantities.</li> <li>OTHERWISE:</li> <li>For potentially moderate exposures:</li> <li>Wear general protective gloves, eg. light weight rubber gloves.</li> <li>For potentially heavy exposures:</li> <li>Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>	
Body protection	See Other protection below	
Other protection	No special equipment needed when handling small quantities. <b>OTHERWISE:</b> ► Overalls.	

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the

computer-generated selection:

CRC 9306 Leather Cleaner Aerosol

Material	CPI
BUTYL	A
NEOPRENE	A
VITON	А
NATURAL RUBBER	С
PVA	С

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis,

factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

**Appearance** White aerosol foam with a pleasant odour; soluble in water. Supplied in an aerosol pack containing a hydrocarbon propellant.

Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul> <li>Elevated temperatures.</li> <li>Presence of open flame.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7

#### **Respiratory protection**

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AX-AUS / Class 1 P2	-
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### SECTION 11 TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Not normally a hazard due to non-volatile nature of product The vapour is discomforting <b>WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.</b> The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Spray mist may produce discomfort
Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Not considered to be a risk because of the extreme volatility of the gas. Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	Spray mist may produce discomfort The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Not considered to be a risk because of the extreme volatility of the gas.
Chronic	Main route of exposure to the gas in the workplace is by inhalation. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

CRC 9306 Leather Cleaner	TOXICITY	IRRITATION	
Aerosol	Not Available	Not Available	
	тохісіту	IRRITATION	
	Dermal (rabbit) LD50: 1780 mg/kg <sup>[2]</sup>	Eye (rabbit): 5 mg SEVERE	
	Oral (rat) LD50: 1310 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	
nonyiphenol, ethoxylated		Skin (human): 15 mg/3D mild	
		Skin (rabbit): 500 mg mild	
		Skin: adverse effect observed (irritating) <sup>[1]</sup>	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg/24h-moderate	
2,6-di-tert-butyl-	Oral (rat) LD50: 890 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
4-methylphenol		Skin (human): 500 mg/48h - mild	
		Skin (rabbit):500 mg/48h-moderate	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	тохісіту	IRRITATION	
water	Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Available	
	тохісіту	IRRITATION	
hydrocarbon propellant	Not Available	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

NONYLPHENOL,<br/>ETHOXYLATEDFor nonylphenol and its compounds:<br/>Alkylphenols like nonylphenol and bisphenol A have estrogenic effects in the body. They are known as xenoestrogens.<br/>Estrogenic substances and other endocrine disruptors are compounds that have hormone-like effects in both wildlife and<br/>humans. Xenoestrogens usually function by binding to estrogen receptors and acting competitively against natural estrogens.<br/>Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They<br/>then form complex mixtures of oxidation products.<br/>Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are<br/>sensitisers. The oxidization products also cause irritation.<br/>Humans have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps,<br/>detergents and other cleaning products. Exposure to these chemicals can occur through swallowing, inhalation, or contact with

2,6-DI-TERT-BUTYL- 4-METHYLPHENOL	Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma. Death may result in experimental animal. For nonylphenol: Animal testing suggests that repeated exposure to nonylphenol may cause liver changes and kidney dysfunction. Nonylphenol was not found to cause mutations or chromosomal aberrations. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to inflants may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to inflants may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to inflants may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to inflants may produce severe irritation to the eye causing pronounced inflammation. Repeated or proven to data show that acute toxicity following oral and topical use of hindered phenols is low. The data show that acute toxicity following oral and topical uses of hindered phenols is low. They are not proven to cause mutations. However, long term use may affect the liver, thyroid, kidney and lymph nodes. Liver tumours have been reported. The substance is classified by IARC as Group 3: NOT Essistile as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to callular DNA. " Degussa SDS Effects such as behavioral changes, reduction in body weight gain, and decrement in body weight have been observed infer Long-term Aministration of HT to mice and rake aceeding methylow-16-CS-26-30 is a very reactive compound which is considered to play a significant role in hepatoxicity, and not only on that of HT. The metabo				
	gastritis after ingesting a high dose of BHT (4 an short-term subchronic toxicity studies, it has bee	nd 80 g without medical prescription reported that BHT causes dose	on) to cure recurrent genital herpes. Regarding e-related increase in the incidence and severi		
HYDROCARBON PROPELLANT	inhalation of the gas				
CRC 9306 Leather Cleaner Aerosol & 2,6-Dl- TERT-BUTYL- 4-METHYLPHENOL	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophila.				
NONYLPHENOL, ETHOXYLATED & 2,6-DI- TERT-BUTYL- 4-METHYLPHENOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.				
WATER & HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature search.				
Acute Toxicity	×	Carcinogenicity	×		
Skin Irritation/Corrosion	×	Reproductivity	×		
Serious Eye Damage/Irritation	× STOT - Single Exposure				

-

×

STOT - Repeated Exposure

Aspiration Hazard ×

-

Legend:

¥ − Data either not available or does not fill the criteria for classification Data available to make classification

### **SECTION 12 ECOLOGICAL INFORMATION**

### Toxicity

CRC 9306 Leather Cleaner Aerosol	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	Not Available	Not Available	Not Available		Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish		1.3mg/L	4
nonylphenol, ethoxylated	EC50	48	Crustacea		12.2mg/L	4
	EC50	96	Algae or other aquatic plants		12.0mg/L	4
	NOEC	2400	Fish		0.035mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish	Fish		2
2,6-di-tert-butyl-	EC50	48	Crustacea	Crustacea >C		2
+-methylphenor	EC50	96	Algae or other aquatic plants		0.228mg/L	3
	NOEC	504	Crustacea		0.023mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	V	ALUE	SOURCE
water	LC50	96	Fish	Fish 897.520r		3
	EC50	96	Algae or other aquatic plants	8	768.874mg/L	3
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish	Fish 24.11r		2
hydrocarbon propellant	EC50	96	Algae or other aquatic plants	Algae or other aquatic plants 7.71mg		2
	LC50	96	Fish	Fish 24.11mg/L		2
	EC50	96	Algae or other aquatic plants		7.71ma/L	2

Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. ECETOC Aquatic Vendor Data

#### For Phenols:

Ecotoxicity - Phenols with log Pow >7.4 are expected to exhibit low toxicity to aquatic organisms however; the toxicity of phenols with a lower log Pow is variable. Dinitrophenols are more toxic than predicted from QSAR estimates. Hazard information for these groups is not generally available. Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.). DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
nonylphenol, ethoxylated	LOW	LOW
2,6-di-tert-butyl- 4-methylphenol	HIGH	HIGH
water	LOW	LOW

### **Bioaccumulative potential**

Ingredient	Bioaccumulation
nonylphenol, ethoxylated	LOW (BCF = 16)
2,6-di-tert-butyl- 4-methylphenol	HIGH (BCF = 2500)
water	LOW (LogKOW = -1.38)

# Mobility in soil

Ind	redi	ient
mg	rea	ient

nonylphenol, ethoxylated	LOW (KOC = 940)
2,6-di-tert-butyl- 4-methylphenol	LOW (KOC = 23030)
water	LOW (KOC = 14.3)

### SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods		
Product / Packaging disposal	<ul> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Discharge contents of damaged aerosol cans at an approved site.</li> <li>Allow small quantities to evaporate.</li> <li>DO NOT incinerate or puncture aerosol cans.</li> </ul>	

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

### **SECTION 14 TRANSPORT INFORMATION**

### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

### Land transport (UN)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	Class     2.2       Subrisk     Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions63; 190; 277; 327; 344; 381Limited quantity1000ml		

# Air transport (ICAO-IATA / DGR)

UN number	1950			
UN proper shipping name	Aerosols, non-flammable			
Transport hazard class(es)	ICAO/IATA Class2.2ICAO / IATA SubriskNot ApplicableERG Code2L			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions		A98 A145 A167 A802 203 150 kg 203 75 kg Y203	

# Sea transport (IMDG-Code / GGVSee)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	IMDG Class     2.2       IMDG Subrisk     Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-D , S-USpecial provisions63 190 277 327 344 381 959Limited Quantities1000 ml		

### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard			
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2017			
NONYLPHENOL, ETHOXYLATED IS FOUND ON THE FOLLOWING REGULATORY LISTS				
Chemical Footprint Project - Chemicals of High Concern List		New Zealand Hazardous Substances and New Organisms (HSNO) Act -		
New Zealand Approved Hazardous Substances with controls		Classification of Chemicals - Classification Data		
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals		New Zealand Inventory of Chemicals (NZIoC)		
2,6-DI-TERT-BUTYL-4-METHYLPHENOL IS FOUND ON THE FOLLOWING REGULATORY LISTS				
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs		New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data		
New Zealand Approved Hazardous Substances with controls		New Zealand Inventory of Chemicals (NZIoC)		
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals		New Zealand Workplace Exposure Standards (WES)		
WATER IS FOUND ON THE FOLLOWING REGULATORY LISTS				
New Zealand Inventory of Chemicals (NZIoC)				
HYDROCARBON PROPELLANT IS FOUND ON THE FOLLOWING REGULATORY LISTS				
Chemical Footprint Project - Chemicals of High Concern List		New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data		
New Zealand Approved Hazardous Substances with controls				

#### **Hazardous Substance Location**

Classification of Chemicals

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

New Zealand Hazardous Substances and New Organisms (HSNO) Act -

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

# **Tracking Requirements**

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (water; hydrocarbon propellant; nonylphenol, ethoxylated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### **SECTION 16 OTHER INFORMATION**

Revision Date	07/03/2020
Initial Date	11/10/2007

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
4.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
5.1.1.1	07/03/2020	Classification change due to full database hazard calculation/update.

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

- PC-STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- **BEI: Biological Exposure Index**

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.