

Therm 1165-1

**TOP
SELLER**



Tidy storage system

Practical stowing of the trigger gun with safety catch and lances

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

Digital operating panel

to control the water temperature and view cold/hot use operating time management

Removable covers

Protect the mechanical components from environmental factors and provide convenient access

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Parking brake

For a secure stationary position

Water output < 1000 l/h

therm 1165-1

Technical specifications		Three Phase	
Operating pressure adjustable	psi	2390	
Max. admissible overpressure	psi	2610	
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12	
Motor speed	Rpm	1400	
Water output	l/min l/h	19.4	1165
kW		5.5	
Volume water tank	l	4	
Hot water output adjustable	°C	12-82	
Steam level	°C	155	
Heating output	kW	78	
Fuel tank	l	35	
Power supply cable	m	7.5	
Dimensions L x W x H	mm	1050 / 800 / 1000	
Weight	kg	220	
Detergent Injector		●	
Equipment			
Hose drum		●	
Steel braided high-pressure hose	m	20	
Trigger gun with safety catch	Model	Starlet	
Stainless steel lance with flat jet nozzle	Nozzle size	● D2507	

2 YEAR
COMMERCIAL
WARRANTY

Brass
Pump Head
10 YEAR
WARRANTY



TECHNICAL HIGHLIGHTS!

DIGITAL THERMOSTAT

The high-pressure cleaners of the therm-1-series are fitted with a digital thermostat which combines a variety of advantages in operation and service.

- Intelligent system analysis
- Reduction of fuel costs thanks to object-specific temperature specification
- Simple reading of the operating hours

Dial a Demo
0800 387 678

