

The therm 1-Series

**TOP
SELLER**



Tidy storage system

Practical stowing of the trigger gun with safety catch and lances

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

**Biggest model
in single phase!**

Digital operating panel

to control the water temperature and view cold/hot use operating time management

Removable covers

Protect the mechanical components from environmental factors and provide convenient access

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Parking brake

For a secure stationary position

		therm 635-1
Technical specifications		Single Phase
Operating pressure adjustable	psi	1885
Max. admissible overpressure	psi	2100
Connected load	V / ~ / Hz / A	230 / 1 / 50 / 15
Motor speed	Rpm	1400
Water output	l/min l/h	10.6 635
kW		2.3
Volume water tank	l	4
Hot water output adjustable	°C	12-89
Steam level	°C	145
Heating output	kW	55
Fuel tank	l	35
Power supply cable	m	5
Dimensions L x W x H	mm	1200 / 800 / 1050
Weight	kg	200
Detergent Injector		●
Equipment		
Hose drum		●
Steel braided high-pressure hose	m	20
Trigger gun with safety catch	Model	Starlet
Stainless steel lance with flat jet nozzle	Nozzle size	● D25045



TECHNICAL HIGHLIGHTS!

DIGITAL THERMOSTAT

The high-pressure cleaners of the therm-1-series are fitted with a digital thermostat which combines a variety of advantages in operation and service.

- Intelligent system analysis
- Reduction of fuel costs thanks to object-specific temperature specification
- Simple reading of the operating hours

