

## Therm 895-1

TOP  
SELLER



**Tidy storage system**  
Practical stowing of the trigger gun with safety catch and lances

**Integrated Hose drum**  
Practical design and features a longer length high-pressure hose complete with folding crank (Version incl. hose drum)

**Digital operating panel**  
to control the water temperature and view cold/hot use operating time management

**Removable covers**  
Protect the mechanical components from environmental factors and provide convenient access

**Cleaning Agent Intake**  
Injector system for dispensing of cleaning agents

**Parking brake**  
For a secure stationary position



Water output < 1000 l/h **therm 895-1**

Technical specifications		Three Phase
Operating pressure adjustable	psi	2830
Max. admissible overpressure	psi	3120
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12
Motor speed	Rpm	1400
Water output	l/min   l/h	14.9   895
kW		5.5
Volume water tank	l	4
Hot water output adjustable	°C	12-86
Steam level	°C	155
Heating output	kW	65
Fuel tank	l	35
Power supply cable	m	7.5
Dimensions L x W x H	mm	1050 / 800 / 1000
Weight	kg	220
Detergent Injector		●
Equipment		
Hose drum		●
Steel braided high-pressure hose	m	20
Trigger gun with safety catch	Model	Starlet
Stainless steel lance with flat jet nozzle	Nozzle size	● D25045

**2 YEAR**  
COMMERCIAL  
WARRANTY

Brass  
Pump Head  
**10 YEAR**  
WARRANTY



### TECHNICAL HIGHLIGHTS!

#### DIGITAL THERMOSTAT

The high-pressure cleaners of the therm-1-series are fitted with a digital thermostat which combines a variety of advantages in operation and service.

- Intelligent system analysis
- Reduction of fuel costs thanks to object-specific temperature specification
- Simple reading of the operating hours

**Dial a Demo**  
0300 387 678

