



VERTEX ANTI-SPATTER WELD SPRAY

SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	VERTEX ANTI-SPATTER WELD SPRAY
Product Use:	Anti-spatter weld spray
Supplier:	Vertex Lubricants
	22 Marphona Crescent
	Takanini 2105
	Phone: 09/640 0004
	Email: info@vertexlubricants.co.nz
Emergency Number:	0800 353 645
Chemical Nature:	Methylene Chloride, Carbon Dioxide
Issue Date:	19 August 2023 and is valid for 5 years from this date.

SECTION 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

HSNO Classifications:

9.1B effects

2.1.2A Flammable Aerosol

6.3A Irritating to the skin6.4A Irritating to the eye

6.7B Suspected human carcinogen

6.9B Harmful to human target organs or systems (chronic)

Ecotoxic in the aquatic environment with long lasting

Classified as a dangerous goods for transport purposes.

GHS Classifications: Aerosol Category 2 Skin irritation Category 2 Eye irritation Category 2 Carcinogenicity Category 2 STOT (chronic) Category 2 Aquatic toxicity (Chronic) Category 2



Signal Words: Danger

- **Hazard Statements**
- H223 Flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 May cause skin irritation.
- H319 May cause serious eye irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice. [®] Vertex is a registered trademark of Lubricants NZ Ltd.





SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Methylene Chloride	75-09-2	> 60
Carbon Dioxide	124-38-9	1 - 10
Non-hazardous ingredients		to 100

SECTION 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Ingestion:	Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

SECTION 5 – FIRE FIGHTING MEASURES

General fire hazards:	Pressurised container, flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. However vapour will burn when in contact with high temperature flame, ignition ceases on removal of flame. May form a flammable or explosive mixture in an oxygen enriched atmosphere. May be violently or explosively reactive.
Further advice:	On burning may emit toxic fumes including those of phosgene, hydrogen chloride, carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus.
Extinguishing media:	Use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.
Protective equipment:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Firefighting instructions:	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE





SECTION 6 – ACCIDENTAL RELEASE MEASURES

Minor spills:	Clean up all spills immediately. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water. Product is extremely slippery, especially when wet.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers for disposal.
SECTION 7 - HAND	DLING AND STORAGE

Handling Precautions: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Read product label before use. Keep out of reach of children. Keep away from heat and open flames. Do not spray on an open flame or other ignition source. This product is highly flammable. Pressurised container: Do not pierce or burn, even after use. No smoking. Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Use outdoors or in a well-ventilated area. Avoid breathing spray or vapours. Wash hands with soap and water after handling.

Storage:Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well-
ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

SECTION 8 – EXPOSURE CONTROLS AND PEROSNAL PROTECTION

Exposure Limits: No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Methylene Chloride (6.7B)	174	-
Carbon Dioxide	9,000	54,000

Additional Information:	Obtain special instructions before use. Wash hands before eating, drinking, and smoking.
Engineering Controls:	No controls generally required when handling small quantities. Use with adequate ventilation. Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion resistant.
Protective Equipment:	General protective gloves are recommended. In an industrial environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.



Material Safety Data Sheet

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Colourless spray with characteristic odour.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	300 - 600
Boiling Point, °C:	About 40
Melting Point, °C:	Not applicable.
Specific Gravity:	About 1.5
Flash Point, °C:	Not determined.
Explosion Limit, % v/v:	LEL 90% UEL 12%
Autoignition Temp, °C:	> 200
Solubility:	Not soluble in water.

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

SECTION 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Acute Oral Toxicity:	Information given is based on product testing, and/or similar products, and/or components. LD_{50} estimated to be > 1,700 mg/kg (based on component mixture, excluding propellant).
Acute Dermal Toxicity:	LD_{50} estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
Acute Inhalation Toxicity:	LC_{50} estimated to be >20 mg/L, Rat 4 hour (based on component mixture).
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
Skin Irritation:	Avoid contact with skin. Moderate irritant to skin.
Eye Irritation:	May cause serious eye irritation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure. Avoid contact with eyes.
Inhalation:	May cause drowsiness or dizziness. Material is highly volatile and may form concentrated levels of vapour. May displace air and act as a simple asphyxiant.
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Sensitisation:	Not expected to be a contact or respiratory sensitiser.
Carcinogenicity:	Components in this product are suspected of causing cancer in humans.
Reproductive toxicity:	Not expected to be toxic.
STOT (Narcotic):	Prolonged inhalation of vapours may be narcotic and cause drowsiness or dizziness.
Repeated Dose Toxicity:	Repeated, prolonged exposure by inhalation may cause damage to organs. Accumulation in the human body may occur and may cause some concern following repeated or long-term occupational exposure.





SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Mobility: Mobility is expected to be low in soil.

Persistence/degradability: Partially biodegradable.

Bioaccumulation Potential: May bioaccumulate.

SECTION 13 - DISPOSAL CONSIDERATION

Material Disposal:Product wastes should be disposed of in accordance with applicable regulations. Do not
dispose into the environment, in drains or in water courses.Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities
of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.Container Disposal:Recycle empty container if possible or dispose in landfill. Product containers are also

considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

SECTION 14 – TRANSPORT INFORMATION

Transport:	Classified as a Dangerous Good for transport purposes. Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
Proper Shipping Name:	Aerosols
UN Number:	1950
Dangerous Goods Class:	2.1
Transport Labels Required:	Class 2 Flammable (Land, Sea, Air), EHSM (Sea and Air)
	Land, Sea, Air MP
Subsidiary Risk:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	Yes
EMS Number DG Segregation:	F-D, S-U (UN 1950 Flammable aerosols) This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

SECTION 15 – REGULATORY INFORMATION

Inventory Listing	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.
SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.

Vertex Lubricants

www.vertexlubricants.co.nz



Material Safety Data Sheet

EPA Approval Number:	HSR002517 Aerosols (Flammable, Carcinogenic) Group Standard 2020.
EPA Hsno Controls:	Refer to <u>www.epa.govt.nz</u> for information on Controls.
	This substance is to be managed using the conditions specified in an applicable Group Standard.

SECTION 16 – OTHER INFORMATION

Additional information: Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health effects from exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC ₅₀	Lethal Concentration, 50% / Median Lethal Concentration
	LD ₅₀	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m³	Milligrams per Cubic Metre
	NZIOC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
	UEL	Upper Explosion Limit

This MSDS contains only safety-related information. For other data see product literature.

MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using the product.